Bizgram Asia Pte Ltd 1 Rochor Canal Road, # 05-49/50
Simlim Square, Level 5, Outside the Central Lift. Singapore
188504.
Tel: 63346455 / 63341373
Fax: 63341615 (10am to 7.30pm All 7 Days)

Model	price	Size	EAN Code	Product Title	Display Panel Diagonal	Panel Type	Backlight Type	Physical Resolution	Display Surface Treatment	Protection Glass	Touch Screen	Pixel Pitch / PPI	Max. Brightness	Color Saturation	Number of Colors
			Display Detail												
VS207DF	$129	19.5"W	4712900474923	ASUS VS207DF, 19.5" Monitor, 1366x768, D-Sub	19.5"(49.5cm) Wide Screen (16:9)	WLED/ TN	WLED	1366x768	Non-glare	–	–	0.318 x 0.307mm	200cd/㎡	72%(NTSC)	16.7M
VX207DE	$132	19.5"W	4716659747178	ASUS VX207DE Eye Care Monitor - 19.5" (1366x768), Flicker free, Low Blue Light	19.5"(49.5cm) Wide Screen (16:9)	WLED/ TN	WLED	1366x768	Non-glare	–	–	0.318 x 0.307mm	200cd/㎡	72%(NTSC)	16.7M
VP228HE	$169	21.5"	4712900545142	ASUS VP228HE Gaming Monitor - 21.5" FHD (1920x1080) , 1ms, Low Blue Light, Flicker Free	21.5" (54.6cm)Wide Screen (16:9)	WLED/ TN	WLED	1920x1080	non-glare	–		0.248mm	200cd/㎡	72%(NTSC)	16.7M
VS239HV	$260	23"W	4716659447832	ASUS VS239HV Monitor - 23" FHD (1920x1080), IPS, HDMI	23" (58.4cm)Wide Screen, 16:9	WLED/ IPS	WLED	1920x1080	non-glare	–		0.2652mm	250cd/㎡	72%(NTSC)	16.7M
VZ239H	$289	23"W	4712900521924	ASUS VZ239H Eye Care Monitor - 23" FHD (1920x1080), IPS, Ultra-Slim Design, Frameless, Flicker free, Low Blue Light	23" (58.4cm)Wide Screen, 16:9	WLED/ IPS	WLED	1920x1080	non-glare	–		0.2652mm	250cd/㎡	72%(NTSC)	16.7M
MX239H	$359	23"W	4716659265757	ASUS Designo MX239H Monitor, 23" FHD (1920x1080), IPS, Audio by Bang & Olufsen ICEpower®, Frameless, Flicker free, Low	23.0"(58.42cm) wide screen(16:9)	WLED/ IPS	WLED	1920x1080	non-glare	–		0.2652mm	250cd/㎡	72%(NTSC)	16.7M
VP247HA	$209	23.6"W	4712900319583	ASUS VP247HA Eye Care Monitor - 23.6" FHD (1920x1080), 178° Wide Viewing Angle, Speakers, Flicker free, Low Blue Light	23.6"(59.9cm) Wide Screen (16:9)	WLED/ VA	WLED	1920x1080	non-glare	–		0.272mm	250cd/㎡	72%(NTSC)	16.7M
VS247HV	$219	23.6"W	4716659591177	ASUS VS247HV 23.6" Monitor, FHD (1920x1080), HDMI, DVI-D, D-Sub	23.6"(59.9cm) Wide Screen (16:9)	WLED/ TN	WLED	1920x1080	non-glare	–		0.272mm	250cd/㎡	72%(NTSC)	16.7M
VS248HR	$219	24"W			24.0"	WLED/ TN	WLED	1920x1080	non-glare			0.272mm	250 cd/㎡	72%(NTSC)	16.7M
VG245H Fre Sync	$339	24"W	4712900413885	ASUS VG245H Gaming Monitor - 24" FHD (1920x1080) 1ms, GameFast Input Technology, FreeSync™	24" (61.0cm)Wide Screen (16:9)	WLED/ TN	WLED	1920x1080(up to 75Hz)	non-glare	-		0.276mm	250cd/㎡	72%(NTSC)	16.7M
VG248QE	$508	24"W	4716659363002	ASUS VG248QE Gaming Monitor -24" FHD (1920x1080) , 1ms, up to 144Hz, 3D Vision Ready	24" (61.0cm)Wide Screen (16:9)	WLED/ TN	WLED	1920x1080(up to 144Hz)	non-glare	–		0.276mm	350cd/㎡	72%(NTSC)	16.7M
PG248Q	$799	24"W	4712900414004	ASUS ROG Swift PG248Q eSports Gaming Monitor - 24" FHD (1920x1080) 1ms, overclockable 180Hz, G-Sync™	24" (61.0 cm) Wide Screen (16:9)	WLED/ TN	WLED	1920x1080(up to 180Hz)	non-glare	–		0.276mm	350cd/㎡	72%(NTSC)	16.7M
PG258Q	$999	24.5"W	4712900589887	ROG Swift PG258Q Gaming Monitor – 24.5" FHD (1920x1080), Native 240Hz, 1ms, G-SYNC™	25" (63.44cm) Wide Screen (16:9)	TN	WLED	1920x1080 (up to 240Hz)	non-glare	–	–	0.283mm	400cd/㎡	72% NTSC	16.7 M
VP278H	$319	27"W	4712900124262	ASUS VP278H Gaming Monitor - 27" FHD (1920x1080), 1ms, Low Blue Light, Flicker Free	27"(68.6cm) Wide Screen (16:9)	WLED/ TN	WLED	1920x1080	non-glare	–		0.311mm	300cd/㎡	72%(NTSC)	16.7M
VZ279H	$429	27"W	4712900459685	ASUS VZ279H Eye Care Monitor - 27 inch, Full HD, IPS, Ultra-slim, Frameless, Flicker Free, Blue Light Filter	27"(68.6cm) Wide Screen (16:9)	WLED/ IPS	WLED	1920x1080	non-glare	–		0.311mm	250cd/㎡	72%(NTSC)	16.7M
MX279HR	$519	27"W	4716659521006	ASUS Designo MX279HR Monitor - 27" FHD(1920x1080), IPS, Audio by Bang & Olufsen ICEpower®, Frameless, Low Blue Light	27.0"(68.6cm) wide screen(16:9)	WLED/ IPS	WLED	1920x1080	non-glare	–		0.311mm	250cd/㎡	72%(NTSC)	16.7M
XG27VQ	$749	Curved 27"W		ROG Strix XG27VQ Curved Gaming Monitor – 27 inch Full HD (1920x1080), 144Hz, Extreme Low Motion Blur, Adaptive-Sync(FreeSync™)	Wide Screen 27.0"(68.47cm)16:9	VA	WLED	1920x1080	Non-glare	–		0.311mm	300 cd/㎡	72%(NTSC)	16.7M
MG279Q	$999	27"W	4712900016451	ASUS MG279Q Gaming Monitor - 27" 2K WQHD (2560 x 1440), IPS, up to 144Hz, FreeSync	27" (68.5 cm) Wide Screen (16:9)	W-LED / In-plane Switching Technology	WLED	2560 x 1440 (up to 144Hz) (DP1.2) 1920 x 1080 at 120Hz (HDMI1.4)	Non-glare	–	–	0.233 mm (109ppi)	350 cd/m²	100% sRGB	16.7M
PG278Q	$1,099	27"W	4716659752462	ROG Swift PG278Q Gaming Monitor - 27" 2K WQHD (2560 x 1440), 1ms, up to 144Hz, G-SYNC™	27" (68.5 cm) Wide Screen (16:9)	WLED / TN	WLED	2D mode : 2560 x 1440 (up to 144Hz) 3D mode : 2560 x 1440 (up to 120Hz) 2D Surround : 7680 x 1440	non-glare	–	–	0.233 mm	350 cd/m²	72% sRGB	16.7M
PB279Q	$1,248	27"W	4716659764670	ASUS PB279Q Professional Monitor - 27" 4K UHD (3840 x 2160), IPS, 100% sRGB, Flicker free, Low Blue Light	27" (68.4cm) Wide Screen (16:9)	WLED/ AHVA (In Plane Switching Technology)	WLED	"3840x2160 (163ppi)@60Hz(DP1.2) 3840x2160 (163ppi)@30Hz(HDMI)"	non-glare	–	–	0.15525mm	300cd/㎡	100% sRGB (NTSC 75%)	1.07B(8 bit + FRC)
PB27UQ	$1,290	27"W	4712900437584	ASUS PB27UQ: 4K Detail. Get Ready For Work and Play: Professional 27" 4K UHD monitor with 3840 x 2160 resolution, 100% sRGB, 10-bit color and 178-degree wide-	27" (68.4cm) Wide Screen (16:9)	WLED/ AHVA (In Plane Switching Technology)	WLED	"3840x2160 (163ppi)@60Hz(DP1.2) 3840x2160 (163ppi)@30Hz(HDMI)"	non-glare	–	–	0.15525mm	300cd/㎡	100% sRGB (NTSC 75%)	1.07B(8 bit + FRC)
PG279Q	$1,359	27"W	4712900162813	ASUS ROG Swift PG279Q Gaming Monitor - 27" 2K WQHD (2560 x 1440) IPS, overclockable 165Hz, G-SYNC™	27" (68.5 cm) Wide Screen (16:9)	WLED/ AHVA (In Plane Switching Technology)	WLED	DP: 2560 x 1440 up to 165Hz. HDMI : 2560 x 1440 @ 60Hz.	non-glare	–	–	0.233 mm	350 cd/m²	100% sRGB	16.7M
PG27AQ	$1,329	27"W	4712900162868	ASUS ROG Swift PG27AQ Gaming Monitor - 27" 4K UHD (3840x2160), IPS, G-SYNC™	27" (68.5 cm) Wide Screen (16:9)	WLED/ AHVA (In Plane Switching Technology)	WLED	DP: 3840 x 2160 up to 60Hz. HDMI: 3840 x 2160 (24 Hz) / 1920 x 1080 (60Hz)	non-glare	–	–	0.155mm	300 cd/m²	100% sRGB	16.7M
PB298Q	$828	29"W	4716659479611	See Wider, Work Smarter: Ultra-wide 21:9 2560 x 1080 resolution AH-IPS Panoramic Monitor	29"(73.025cm) Wide Screen (21:9)	WLED/AH-IPS	WLED	2560 x 1080	non-glare	–		0.2628mm	300cd/㎡	72%(NTSC)	16.7M
PA328Q	$2,136	32" W	4716659919568	ASUS ProArt PA328Q Professional Monitor - 32" 4K UHD(3840 x 2160), IPS, Color Accuracy ΔE< 2, Flicker free	32" (81.28cm) Wide Screen (16:9)	In-plane Switching Technology (AHVA)	W-LED	3840 x 2160 at 60Hz (DP1.2) 3840 x 2160 at 60Hz (HDMI2.0) 3840 x 2160 at 30Hz (HDMI1.4)	Non-glare	–	–	0.1845 mm (138 ppi)	350 cd/m²	100% sRGB	1073.7 M (10 bits)
PA329Q	$2,299	32" W	4712900270662	ASUS ProArt PA329Q Professional Monitor - 32" 4K UHD(3840 x 2160), IPS, Quantum Dot, 99.5% Adobe RGB, Hardware Calibration, Color Accuracy ΔE< 2	32" (81.28cm) Wide Screen (16:9)	In-plane Switching Technology (AHVA)	W-LED	3840 x 2160 at 60Hz (DP1.2) 3840 x 2160 at 60Hz (HDMI2.0)	Non-glare	–	–	0.1845 mm (138 ppi)	Typ. 300 cd/m²	99.5% AdobeRGB	1073.7 M (10 bits)
PG348Q	$1,699	34"W CURVE	4712900261516	ASUS ROG Swift Curved PG348Q Gaming Monitor - 34" 21:9 Ultra-wide QHD (3440x1440), overclockable 100Hz , G-SYNC™	34" (86.72cm) Wide Screen 21:9	IPS, In-plane Switching Technology	W-LED	3440x1440 at 100Hz (DP1.2) 3440x1440 at 50Hz (HDMI1.4)	Non-glare	–	–	0.2325 mm (109 ppi)	300 cd/m²	100% sRGB	1073.7 M (10 bits)
MX34VQ	$1,598	34"W CURVE	4712900494242	ASUS Designo Curve MX34VQ Ultra-wide Curved Monitor - 34 inch, UWQHD, 1800R Curvature, Frameless, Qi Wireless Charger, Audio by Harman Kardon, Flicker Free,	34" (86.72cm) Wide Screen 21:9	VA	W-LED	3440x1440	Non-glare	–	–	0.2325 mm (109 ppi)	300 cd/m²	72% NTSC	1073.7 M (10 bits)
MB169B+	$339	15.6"W	4712900071122	ASUS MB169B+ Portable monitor - 15.6" FHD (1920x1080), USB-powered, IPS, Ultra-slim, Auto-rotatable	15.6"(39.6cm) W (16:9)	WLED/IPS	WLED	1920x1080	Non-glare	–		0.179mm	250cd/㎡	60%(NTSC)	262,144
MB16AC	$449	15.6"W	4712900680669	ASUS ZenScreen MB16AC portable monitor-15.6" FHD (1920x1080), USB Type-C, IPS	15.6"(39.6cm) W (16:9)	WLED/IPS	WLED	1920x1080	Non-glare	–		0.179mm	250cd/㎡	45%(NTSC)	262,144

Model	Max. Contrast Ratio / Max. Native Contrast Ratio	Viewing Angle as CR ≥ 10	Response Time	Full HD 1080p Support	HDCP Support	Trace Free Technology	SPLENDID™ Preset Mode	Color Temperature Selection	Skin-Tone Selection	Picture-in-Picture	Built-in Webcam	Speaker	QuickFit	GamePlus	Analog Signal Frequency	Digital Signal Frequency
	Display Detail														Signal Frequency	
VS207DF	10,000,000:1/600:1	90°(H)/65°(V)	5ms	–	–	–	6 modes	4 modes	3 modes	–	–	–	2 modes (Alignment Grid/ Photo)	–	30~83 KHz(H)/ 50~75 Hz(V)	–
VX207DE	10,000,000:1/600:1	90°(H)/65°(V)	5ms	–	–	–	8 modes	4 modes	3 modes	–	–	–	2 modes (Alignment Grid/ Photo)	–	30~83 KHz(H)/ 50~76 Hz(V)	30~83 KHz(H)/ 50~76 Hz(V)
VP228HE	100,000,000:1 /1000:1	170°(H)/160°(V)	1ms(GTG)	Yes	Yes	Yes	8 modes	4 modes	3 modes	–	–	1.5W x 2, RMS	3 modes (Alignment Grid 1/ Alignment Grid 2/	2 modes: Aimpoint, Timer	30~80 KHz(H)/ 50~75 Hz(V)	30~80 KHz(H)/ 50~75 Hz(V)
VS239HV	80,000,000:1/1,000:1	178°(H)/178°(V)	5ms (GTG)	Yes	Yes	–	6 modes	4 modes	3 modes	–	–	–	3 modes(Alignment Grid / Letter /Photo)	–	30~83 KHz(H)/ 50~75 Hz(V)	30~83 KHz(H)/ 50~75 Hz(V)
VZ239H	80,000,000:1/1,000:1	178°(H)/178°(V)	5ms (GTG)	Yes	Yes	–	8 modes	4 modes	3 modes	–	–	"1.5W x2 stereo, RMS	3 modes(Alignment Grid / Letter /Photo)	2 modes: Aimpoint, Timer	30-80KHz (H) / 56-76Hz (V)	30-80KHz (H) / 56-76Hz (V)
MX239H	80,000,000:1/1, 000:1	178°(H)/178°(V)	5ms (GTG)	Yes	Yes	Yes	6 modes	4 modes	3 modes	–	–	3W x 2, RMS, with 5Wx2 Amplifier, SonicMas	3 modes (Letter/ Alignment Grid/ Photo)	–	28~83 KHz(H)/ 50~75 Hz(V)	28~83 KHz(H)/ 50~75 Hz(V)
VP247HA	80,000,000:1/3000:1	178°(H)/178°(V)	5ms(GTG)	Yes	Yes	Yes	8 modes	4 modes	3 modes	–	–	1.5Wx2, RMS	7 modes (Alignment Grid1 / Alignment Grid 2 / A4 /	2 modes: Aimpoint, Timer	30~80 KHz(H)/ 55~75 Hz(V)	30~80KHz(H) / 55~75Hz(V)
VS247HV	50,000,000:1/1000:1	170°(H)/160°(V)	5ms	Yes	Yes	–	6 modes	4 modes	3 modes	–	–	–	–	–	30~80 KHz(H)/ 55~75 Hz(V)	30~80 KHz (H)/ 55~75 Hz(V)
VS248HR	50,000,000:1/ 1000:1	170°(H)/160°(V)	1ms (GTG)	Yes	Yes	-	6 modes	4 modes	3 modes						30~83 KHz(H)/ 50~76 Hz(V)	30~83 KHz(H)/ 50~76 Hz(V)
VG245H Fre Sync	80,000,000:1 /1000:1	170°(H)/160°(V)	1ms(GTG)	Yes	Yes	Yes(Trace Free II)	6 modes	4 modes	3 modes	–	–	2W x 2, RMS		2 modes:Aimpoint, Timer		VGA:30~90 KHz(H)/ 50~76 Hz(V) HDMI:30~90 KHz(H)/ 40~75
VG248QE	80,000,000:1 /1000:1	170°(H)/160°(V)	1ms(GTG)	Yes	Yes	Yes(Trace Free II)	6 modes	4 modes	3 modes	–	–	2W x 2, RMS	–	2 modes:Aimpoint, Timer	–	HDMI:30~83KHz(H)/ 50~76Hz(V) DP/DVI:30~140KHz(H)/ 50~144Hz(V),
PG248Q	80,000,000:1 /1000:1	170°(H)/160°(V)	1ms(GTG)	Yes	Yes	Yes(Trace Free II)	GameVisual: Scenery, FPS, RTS/RPG, sRGB, Racing, Cinema,User	4 modes	3 modes	–	–	2W x 2, RMS	–	3 Modes, Crosshair / Timer/ FPS Counter	–	24~89KHz(H) / 50~75Hz(V)
PG258Q	80,000,000:1 /1000:1	170°(H)/160°(V)	1ms (Gray to Gray)	Yes	Yes	Yes	GameVisual (FPS,RTS/RPG, Racing, sRGB, Cinema, Standard modes)	4 modes (Cool/Normal/ Warm/User)	3 modes	–	–	–	–	3 Modes, Crosshair / Timer/ FPS Counter	–	DP: 67~255KHz (H) / 30~240Hz (V) HDMI: 30~90KHz (H) / 24~60Hz (V)
VP278H	80000000:1 /1200:1	170°(H)/160°(V)	1ms(GTG)	Yes	Yes	Yes	8 modes (Scenery/ Standard/ Thearter/ game/ Night view/ sRGB/ Reading/ Darkroom)	4 modes	3 modes	–	–	2W x 2, RMS	7 modes (A4 / B5 / Letter/ Alignment Grid 1 / Alignment	–	24~83kHz (H)/ 50~75 Hz (V)	24~83kHz (H)/ 50~75 Hz (V)
VZ279H	80000000:1 /1000:1	178°(H)/178°(V)	5ms (Gray to Gray)	Yes	Yes	Yes	8 modes (Scenery/ Standard/ Thearter/ game/ Night view/ sRGB/ Reading/ Darkroom)	4 modes	3 modes	–	–	1.5W x 2, RMS	3 modes (Alignment Grid/Letter / Photo)	–	30~83kHz (H)/ 50~76 Hz (V)	30~83kHz (H)/ 50~76 Hz (V)
MX279HR	80,000,000:1/1, 000:1	178°(H)/178°(V)	5ms (GTG)	Yes	Yes	Yes	6 modes	4 modes	3 modes	–	–	3W x 2, RMS, with 5Wx2 Amplifier, SonicMas	4 modes (A4/ Letter/ Alignment Grid/ Photo)	–	30~80 KHz(H)/ 56~76 Hz(V)	30~80 KHz(H)/ 56~76 Hz(V)
XG27VQ	100000000:1	178°(H)/178°(V)	4ms (Gray to Gray)	Yes	Yes	Yes	8 Modes(Scenery/Racing/Cinema/RTS/RPG/FPS/sRGB Modes/MOBA	4 modes								Display port 55.3~162 KHz(H) / 48~144Hz(V)
MG279Q	10000000:1 /1000:1	'178°(H)/178°(V)	4ms (GTG)	Yes	Yes	Yes	GameVisual (GameVisual: FPS,RTS/RPG, Racing , sRGB, Cinema, Standard modes)	4 modes	3 modes	–	–	2W x 2, RMS	–	Yes	51.2~221.97KHz(H) /35~144Hz(V)	51.2~221.97KHz(H) /35~144Hz(V)
PG278Q	10000000:1 /1000:1	170°(H)/160°(V)	1ms (GTG)	Yes	Yes	Yes	–	4 modes	–	–	–	–	–	Yes	–	24~89kHz(H) / 50~75Hz(V)
PB279Q	100,000,000:1	178°(H)/178°(V)	5ms (Gray to Gray)	Yes	Yes	Yes	8 modes	4 modes	3 modes	YES(PbP supports up to four UHD sources)	–	2W x 2	3 modes(Document/ Alignment Grid/ Photo)	Yes	–	24~160KHZ(H) / 23~80HZ(V)
PB27UQ	100,000,000:1	178°(H)/178°(V)	5ms (Gray to Gray)	Yes	Yes	Yes	8 modes	4 modes	3 modes	YES(PbP supports up to four UHD sources)	–	2W x 2	3 modes(Document/ Alignment Grid/ Photo)	Yes	–	24~160KHZ(H) / 23~80HZ(V)
PG279Q	10000000:1 /1000:1	178°(H)/178°(V)	4ms (GTG)	Yes	Yes	Yes	–	4 modes	–	–	–	2W*2	–	Yes	–	DP: 34~209KHz(H) /30~165Hz(V) HDMI: 30~140KHz(H) / 24~60Hz(V)
PG27AQ	10000000:1 /1000:1	178°(H)/178°(V)	4ms (GTG)	Yes	Yes	Yes	–	4 modes	–	–	–	2W*2	–	Yes	–	DP: 50~133KHz(H) /30~60Hz(V) HDMI: 30~140KHz(H) / 24~60Hz(V)
PB298Q	80,000,000:1 /1000:1	178°(H)/178°(V)	5ms (GTG)	Yes	Yes	Yes	6 modes	4 modes	3 modes	–	–	3W x 2, RMS	3 modes (Letter/ Alignment Grid/ Photo)	–	–	26~83 KHz(H)/ 24~76 Hz(V)
PA328Q	100,000,000:1 /1000:1	178°(H)/178°(V)	6ms(GTG)	Yes	Yes (HDMI2.0 supports HDCP1.4 & 2.2, Other ports only support HDCP1.4)	Yes	7 Modes (Standard/sRGB/Scenery/Darkroom/Reading/User mode1/User mode2)	4 modes (9300K/6500K /5500K, 5000K)	–	Yes (Picture-by-Picture **2 inputs), Picture-in-Picture)	–	3W x 2 stereo, RMS	Yes	–	–	30~135 kHz (H)/ 24~76 Hz (V)
PA329Q	100,000,000:1 /1000:1	178°(H)/178°(V)	5ms(GTG)	Yes	Yes	Yes	8 Modes (Standard/sRGB/AdobeRGB/Scenery/Darkroom/Reading/User mode1/User mode2)	4 modes (9300K/6500K /5500K, 5000K)	–	Yes (up to 4 windws)	–	3W x 2 stereo, RMS	Yes* New QuickFit	–	–	30~135 kHz (H)/ 24~76 Hz (V)
PG348Q	100,000,000:1 /1000:1	178°(H)/178°(V)	5ms(GTG)	Yes	Yes	Yes	GameVisual (FPS,RTS/RPG, Racing , sRGB, Cinema, Standard modes)	4 modes (9300K/6500K /5500K, 5000K)	–	–	–	2W x 2 stereo, RMS		Yes (Crosshair, Timer, FPS Counter)	–	DP: 73~88KHz(H) / 30~100Hz (V) HDMI: 30~140KHz(H) / 24~60Hz (V)
MX34VQ	100,000,000:1 /1000:1	178°(H)/178°(V)	5ms(GTG)	Yes	Yes	Yes	–	4 modes (9300K/6500K /5500K, 5000K)	–	–	–	8W x 2 stereo, RMS		Yes (Crosshair, Timer, FPS Counter)	–	30~151 KHz (H) / 48~100 Hz (V)
MB169B+	--/600:1	160°(H)/160°(V)	11ms	Yes	Yes	–	–	–	–	–	–	–	–	–	–	–
MB16AC	800:1	178°(H)/178°(V)	5ms	Yes	Yes	–	6 modes	4 modes	3 modes	–	–	–	–	–	–	–

Model	Power Supply Type	Power Rating	Operating Power Consumption	Standby Power Consumption	Chassis Color	Tilt	Swivel	Pivot	Height Adjustment	VESA Wall Mount	Kensington Lock	Signal Input	PC Audio Input	AV Audio Input	AV Audio Output	Earphone Jack	Card Reader	USB port(s)
	Power				Mechanical Design							I/O						
VS207DF	Built-in Power Supply	100~240V, 50 / 60 Hz	<14W	<0.5W	Black	+20° ~ -5°	–	–	–	75 x 75mm	Yes	D-Sub	–	–	–	–	–	–
VX207DE	External Power Adapter	100~240V, 50 / 60 Hz	<13.96W	<0.5W	Black	+20° ~ -5°	–	–	–	–	Yes	D-Sub	–	–	–	–	–	–
VP228HE	Built-in Power Supply	100~240V, 50 / 60 Hz	<21.1W*	<0.5W	Black	+20° ~ -5°	–	–	–	100 x 100mm	Yes	HDMI, DVI, D-Sub	–	HDMI	–	–	–	–
VS239HV	Built-in Power Supply	100~240V, 50 / 60 Hz	<22W*	<1W	Black	+20° ~ -5°	–	–	–	100 x 100mm	Yes	HDMI ,DVI-D, D-Sub	–	HDMI	–	3.5mm Mini-jack	–	–
VZ239H	External Power Adapter	100~240V, 50 / 60 Hz	<24W*	<0.5W	Black	+20° ~ -5°	–	–	–	–	Yes	HDMI ,D Sub	–	HDMI	–	–	–	–
MX239H	External Power Adapter	100-240v, 50/60 Hz	<22W*	<0.5W	Silver+Black	+20°~ -5°	–	–	–	–	Yes	HDMI x 2, D-Sub	3.5mm Mini-jack	HDMI	–	3.5mm Mini-jack	–	–
VP247HA	Built-in Power Supply	100~240V, 50 / 60 Hz	<22.7W*	<0.5W	Black ; Non-Glossy Bezel	+20° ~ -5°	–	–	–	100 x 100mm	Yes	D-Sub, HDMI	–	HDMI	–	–	–	–
VS247HV	Built-in Power Supply	100~240V, 50 / 60 Hz	<22.7W*	<0.5W	Black ; Non-Glossy Bezel	+20° ~ -5°	–	–	–	100 x 100mm	Yes	HDMI ,DVI-D, D-Sub	–	HDMI	–	3.5mm Mini-jack	–	–
VS248HR	Built-in Power Supply	100~240V, 50 / 60 Hz	<23.2W*	<0.5W	Black	+20°~ -5°			-	100 x 100mm	Yes	HDMI, DVI-D & D-Sub	-	HDMI	-	3.5mm Mini-jack (for HDMI only)	-	-
VG245H Fre Sync	External Power Adapter	100-240V, 50 /60Hz	<16.2W	<0.5W	Black	+33° ~ -5°	+90°~-90°	+90°~-90°	Yes(0~130mm)	100 x 100mm	Yes	D-Sub, HDMI*2	3.5mm Mini-jack	HDMI		3.5mm Mini-jack(for HDMI & DP only)		
VG248QE	Built-in Power Supply	100-240V, 50 /60Hz	<45W	<0.5W	Black	+15° ~ -5°	+45°~-45°	90°(clockwise)	Yes(0~110mm)	100 x 100mm	Yes	DisplayPort, HDMI, Dual Link	3.5mm Mini-jack	HDMI	–	3.5mm Mini-jack(for HDMI & DP only)	–	–
PG248Q	External Power Adapter	100~240V, 50 / 60 Hz	<65W	<0.5W	Black	+15° ~ -5°	+45°~-45°	90°(clockwise)	Yes(0~110mm)	100 x 100mm	Yes	DisplayPort, HDMI	3.5mm Mini-jack	–	–	3.5mm Mini-jack		USB3.0 ports(Upstream x 1, Downstr
PG258Q	External Power Adapter	100~240V, 50 / 60 Hz	<65W	<0.5W	Black	+20° ~ -5°	+60°~-60°	0° ~ +90°	Yes(0~120mm)	100 x 100mm	Yes	DisplayPort1.2, HDMI1.4	3.5mm Mini-jack	–	–	3.5mm Mini-jack(for HDMI & DP only)	–	USB3.0 ports(Upstream x 1, Downstr
VP278H	Built-in Power Supply	100~240V, 50 / 60 Hz	<29.1W	<0.5W	Black	+20° ~ -5°	–	–	–	100 x 100mm	Yes	HDMI x 2, D-Sub	3.5mm Mini-jack	HDMI	–	–	–	–
VZ279H	External Power Adapter	100~240V, 50 / 60 Hz	<29W	<0.5W	Black	+20° ~ -5°	–	–	–	–	Yes	HDMI x 2, DVI	3.5mm Mini-jack	HDMI	–	–	–	–
MX279HR	External Power Adapter	100~240V, 50 / 60 Hz	<29.1W*	<0.5W	Silver+Black	+20°~ -5°	–	–	–	–	Yes	HDMI x 2, D-Sub	3.5mm Mini-jack	HDMI	–	3.5mm Mini-jack(for HDMI & DP only)	–	–
XG27VQ	External Power Adapter	100~240V, 50 / 60 Hz			Black	+20°~ -5°	+50°~-50°		0~100 mm	–	Yes	HDMI(v1.4), DisplayPort 1.2, Dual-link	3.5mm Mini-jack	–	–	'Yes (3.5mm Mini-jack)	–	–
MG279Q	Built-in Power Supply	100~240V, 50 / 60 Hz	<38.7W*	<0.5W	Black	+20°~ -5°	+60° ~ -60°	90°(clockwise)	Yes(0~150 mm)	100 x 100mm	Yes	DisplayPort1.2, mini-DisplayPort1.2,	3.5mm Mini-jack	HDMI1.4	–	'Yes (3.5mm Mini-jack)	–	USDB3.0 ports(Upstream x 1, Downstream x 2 /
PG278Q	External Power Adapter	100~240V, 50 / 60 Hz	≦90W*	<0.5W	Black	+20°~ -5°	+60° ~ -60°	90°(clockwise)	Yes(0~120 mm)	100 x 100mm	Yes	DisplayPort	–	–	–	–	–	USDB3.0 ports(Upstream x 1, Downstream x 2)
PB279Q	Built-in Power Supply	90-264V, 50 / 60 Hz	<90W	<0.5W	Black	+20°~ -5°	+60°~-60°	90°(clockwise)	Yes(0~150mm)	100 x 100mm	Yes	DisplayPort 1.2, MiniDP, HDMI 1.4/MHL	3.5mm Mini-jack	–	–	3.5mm Mini-jack	–	–
PB27UQ	Built-in Power Supply	90-264V, 50 / 60 Hz	<90W	<0.5W	Black	+20°~ -5°		90°(clockwise)	Yes(0~150mm)	100 x 100mm	Yes	DisplayPort 1.2, MiniDP, HDMI 1.4/MHL	3.5mm Mini-jack	–	–	3.5mm Mini-jack	–	–
PG279Q	External Power Adapter	100~240V, 50 / 60 Hz	≦90W*	<0.5W	Black	+20°~ -5°	+60° ~ -60°	90°(clockwise)	Yes(0~120 mm)	100 x 100mm	Yes	DisplayPort, HDMI , USB3.0*2	3.5mm Mini-jack	–	–	3.5mm Mini-jack	–	USDB3.0 ports*2
PG27AQ	External Power Adapter	100~240V, 50 / 60 Hz	≦90W*	<0.5W	Black	+20°~ -5°	+60° ~ -60°	90°(clockwise)	Yes(0~120 mm)	100 x 100mm	Yes	DisplayPort, HDMI , USB3.0*2	3.5mm Mini-jack	–	–	3.5mm Mini-jack	–	USDB3.0 ports*2
PB298Q	Built-in Power Supply	100~240V, 50 / 60 Hz	<31.7W*	<0.5W	Black	+20°~ -5°	+60°~-60°	90°(clockwise)	Yes(0~150mm)	100 x 100mm	Yes	DisplayPort, HDMI, Dual-link	3.5mm Mini-jack	HDMI	–	3.5mm Mini-jack(for HDMI & DP only)	–	–
PA328Q	Built-in Power Supply	100-240V, 50/60Hz	<138.3W*	<0.5W	Black	+20° ~ -5°	+60°~-60°	90°(clockwise)	Yes(0~130 mm)	100 x 100mm	Yes	DisplayPort1.2, mini-DisplayPort1.2,	3.5mm Mini-jack	HDMI1.4 /HDMI2.0	–	'Yes (3.5mm Mini-jack)	–	USB3.0 ports(Upstream x 1, Downstream x 4)
PA329Q	Built-in Power Supply	100-240V, 50/60Hz	<138.3W*	<0.5W	Black	+20° ~ -5°	+60°~-60°	90°(clockwise)	Yes(0~130 mm)	100 x 100mm	Yes	DisplayPort1.2, mini-DisplayPort1.2,	3.5mm Mini-jack	HDMI2.0	–	'Yes (3.5mm Mini-jack)	–	USB3.0 ports(Upstream x 1, Downstream x 5)
PG348Q	External Power Adapter	100-240V, 50/60Hz	<100W*	<0.5W	Armor Titanium and Plasma Copper	+20° ~ -5°	+60°~-60°	–	Yes(0~115 mm)	100 x 100mm	Yes	DisplayPort1.2, HDMI1.4	3.5mm Mini-jack	HDMI 1.4	–	'Yes (3.5mm Mini-jack)	–	USB3.0 ports(Downstream x 4)
MX34VQ	External Power Adapter	100-240V, 50/60Hz	<100W*	<0.5W	Space Gray + Black	+20° ~ -5°	–	–	–	100 x 100mm	Yes	DisplayPort1.2, HDMI2.0 x3	3.5mm Mini-jack	HDMI 2.0	–	'Yes (3.5mm Mini-jack)	–	–
MB169B+	NA	5V	<5W	0W	Black	–	–	Yes	–	–	–	USB 3.0	–	–	–	–	–	–
MB16AC	NA	5V	<8W	0W	Black	–	–	Yes	–	–	–	USB 3.0 USB-C	–	–	–	–	–	USB-C

Model	Accessories	Regulation Approvals	Set Dimension (HxWxD)	Phys. Dimension (w/o Stand, HxWxD)	Box Dimension (HxWxD)	Weight (Net)	Weight (Gross)			
	Others		Dimension			Weight				
VS207DF	Power cord, VGA cable, QSG, Warranty Card	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, C-Tick, VCCI, ISO-9241-307(Option), PSE, J-MOSS, Taiwan Green Mark(Option), HF(Option), RoHS, WEEE, Windows 7 and Win8 WHQL, CEL	468.0x355.5x185.0mm	468.0x287.5x45.0 mm	530x412 x115mm	2.59kg	TBD			
VX207DE	Power adapter (33W or 40W), Power cable 1M (optional if adapter is 40W) VGA cable(1.5m), Warranty card, QSG	Energy Star 6.0, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, C-Tick, VCCI, RoHS, WEEE, Windows 7 /8 WHQL, ISO 9241-307, MEPS, J-MOSS	466.9 x 349.2 x 189.96 mm	466.9 x 276.8 x 36.9 mm	528 x 420 x 138 mm	2.3kg	TBD			
VP228HE	VGA cable, Audio Cable, Power cord, Warranty card, Quick start guide	Energy Star® , UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, PSE, J-MOSS, RoHS, WEEE, Windows Vista and Windows 7 WHQL,EPEAT(by country)	513mm x 373mm x 199.4mm	NA	513mm x 309mm x 52.1mm	3.5kg	5.3kg			
VS239HV	Power cord, VGA cable, DVI cable, Warranty card, QSG	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, C-Tick, VCCI, RoHS, WEEE, Windows 7 & Windows 8 WHQL,PSB, J-Moss, CEL Level 1, TCO6.0	552x400.3x200mm	552.8x334x45mm	608x 460 x130 mm	3.5kg	5.9kg			
VZ239H	Power cord, VGA cable, Audio cable, Warranty card, QSG	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, C-Tick, VCCI,China Energy Label Level 1, RoHS, WEEE, Windows 7/8.1/10 WHQL, EPEAT(by country)	531 x 387 x 211 mm	531 x 319 x 37 mm	597 x 500 x125 mm	2.7 kg	4.2kg			
MX239H	65W Power adapter, Power cord, VGA cable, HDMI-to-DVI cable, Warranty card, Quick start guide, Audio cable	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, , J-MOSS, PSE, RoHS, WEEE, Windows 7 & Windows 8 WHQL, EPEAT(by country)	522.2 x 392.2 x 207.2 mm	N/A	615 x 472 x 131 mm	3.7 kg	6.1 kg			
VP247HA	VGA cable, Audio cable, Power cord, Warranty card, Quick start guide	Energy Star® , UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, RoHS, WEEE, Windows Vista and Windows 7 WHQL, EPEAT(by country)	561.1mm x 400.1mm x	N/A	561.1mm x 335.8mm x	4.0kg	5.8kg			
VS247HV	DVI cable, VGA cable, , Power cord, Warranty card, Quick start guide	Energy Star® , UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, RoHS, WEEE, Windows Vista and Windows 7 WHQL , EPEAT(by country)	561.8x410.6x200 mm	561.8x343x45mm	618x 469 x130 mm	4.4kg	6.8kg			
VS248HR										
VG245H Fre Sync	DVI-DL cable, Audio cable, Power cord, Warranty card, Quick start guide, Support CD	Energy Star® , UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, , J-MOSS, PSE, RoHS, WEEE, Windows 7/Windows 8 WHQL, EPEAT(by country), KCC	569.4x499.9x231 mm	569.4x340.4x57.3 mm	674x413 x221mm	5.5kg	8.1kg			
VG248QE	DVI-DL cable, Audio cable, Power cord, Warranty card, Quick start guide, Support CD	Energy Star® , UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, , J-MOSS, PSE, RoHS, WEEE, Windows 7/Windows 8 WHQL, EPEAT(by country), KCC	569.4x499.9x231 mm	569.4x340.4x57.3 mm	674x413 x221mm	5.5kg	8.1kg			
PG248Q	Power cord, DisplayPort cable, HDMI Cable, Warranty Card, Quick start guide, Support CD	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, C-Tick, VCCI, PSE, CEL Level 1, J-MOSS, RoHS, WEEE, Windows 7 / 8.1 / 10 WHQL , KCC, E-Standby, TUV-Flicker Free, TUV-Low Blue Light	561.6 x (418.2 ~ 538.2) x 237.9 mm	561.6 x 329.7 x 70 mm	735 x 415 x 280 mm	6.6Kg	9.5Kg			
PG258Q	Power cord, Power adapter, DisplayPort cable, HDMI cable, USB 3.0 cable , Warranty Card , Quick start guide, Support CD	UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, RCM, VCCI, PSE, CEL Level 1, J-MOSS, RoHS, WEEE, Windows 7/8.1/10 WHQL, KCC, E-STANDBY, TUV-Flicker Free, TUV-Low Blue Light	564.1 x (383.7 ~ 503.7) x 253.7 mm	564.1 x 330.6 x 72.5mm	661 x 443 x 239 mm	5.6Kg	7.9Kg			
VP278H	Audio cable. VGA cable, QSG, Warranty card	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, RoHS, WEEE, Windows 8/Windows 7 WHQL, PSE, EPEAT(by country)	641.4x444.5x219.4mm	641.4x383.1x55mm	704x520 x150mm	4.8kg	7.2Kg			
VZ279H	Adapter, audio cable. VGA cable, DVI Cable, Audio Cable, QSG, Warranty card	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, RoHS, WEEE, Windows 8/Windows 7 WHQL, PSE, EPEAT(by country)	622.6 x 441.3 x 210.1mm	622.6 x 441.3 x 185mm	685 x 500 x 126mm	4.6kg	7.0Kg			
MX279HR	65W Power adapter, Power cord, VGA cable, HDMI-to-DVI cable, Warranty card, QSG, Audio cable	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, , J-MOSS, PSE, RoHS, WEEE, Windows 7 & Windows 8 WHQL, EPEAT(by country)	622.6 x 441.3 x 225.2 mm	N/A	700 × 537 × 114 mm	5.2kg	8.0kg			
XG27VQ		Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, , J-MOSS, PSE, RoHS, WEEE, Windows 7 & Windows 8 WHQL, EPEAT(by country)	752x560 x268mm	619.64x371.12x109mm	752x560 x268mm	6.9 kg	9.95 kg			
MG279Q	Power Cord, DisplayPort-to-miniDP cable, USB 3.0 cable (optional), MHL cable (optional), DisplayPort cable (optional), HDMI cable (optional), Warranty Card,	Energy Star 6.0, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU(EAC), C-Tick, VCCI, J-MOSS, PSE, RoHS, WEEE, Windows 7 / 8.1 WHQL	625 x 559 x 238 mm	625 x 368 x 63 mm	753 x 452 x 224 mm	7.3 kg	10.5 kg			
PG278Q	Power adapter, Power cord, DisplayPort cable, USB3.0 cable, Warranty Card, Quick start guide, Support CD	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, C-Tick, VCCI, PSE, CEL Level 1, J-MOSS, RoHS, WEEE, Windows 7 & 8 WHQL	619.7 x 362.96 x 65.98 mm	619.77 x 362.96 x 237.9 mm	756 x 456 x 300 mm	7.0kg	10.52kg			
PB279Q	Power cord, Audio cable, Warranty card (5 regions), QSG , HDMI1.4cable(optional), DP 1.2 cable(optional),MHL cable(optional)	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, C-Tick, VCCI,China Energy Label Level 1, RoHS, WEEE, Windows 7/8 WHQL, PSE,MEPS,TCO6.0, CU, KCC	624.96x407.76x220.06 mm	624.96x368.23x58.8 mm	753x452 x224 mm	7.7kg	10kg			
PB27UQ	Power cord, Audio cable, Warranty card (5 regions), QSG , HDMI1.4cable(optional), DP 1.2 cable(optional),MHL cable(optional)	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, C-Tick, VCCI,China Energy Label Level 1, RoHS, WEEE, Windows 7/8 WHQL, PSE,MEPS,TCO6.0, CU, KCC	624.96x407.76x220.06 mm	624.96x368.23x58.8 mm	753x452 x224 mm	7.7kg	10kg			
PG279Q	Power cord, DisplayPort cable, HDMI Cable, USB3.0 cable, Warranty Card, Quick start guide, Support CD	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, C-Tick, VCCI, PSE, CEL Level 1, J-MOSS, RoHS, WEEE, Windows 7 / 8.1 / 10 WHQL , KCC, E-Standby, TUV-Flicker Free, TUV-Low Blue Light	619.7 x 362.96 x 65.98 mm	619.77 x 552.53 x 237.9 mm	756 x 456 x 300 mm	7.2kg	10.7kg			
PG27AQ	Power cord, DisplayPort cable, HDMI Cable, USB3.0 cable, Warranty Card, Quick start guide, Support CD	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, C-Tick, VCCI, PSE, CEL Level 1, J-MOSS, RoHS, WEEE, Windows 7 / 8.1 / 10 WHQL , KCC, E-Standby, TUV-Flicker Free, TUV-Low Blue Light	619.7 x 362.96 x 65.98 mm	619.77 x 552.53 x 237.9 mm	756 x 456 x 300 mm	7.2kg	10.7kg			
PB298Q	Power Cord, Dual-link DVI Cable, HDMI Cable, DisplayPort Cable, Audio Cable, Quick Start Guide, Warranty Card, Cable Clip	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, RoHS, WEEE, Windows 7 and 8 WHQL, TCO 6.0, PSE, EPEAT(by country)	700x376 x218mm	699.79 x 319.7 x 62.5mm	804 x 437 x 253 mm	8.5kg	12.2kg			
PA328Q	Power Cord, DisplayPort-to-mini DisplayPort cable, HDMI cable, MHL cable (optional), USB 3.0	Energy Star 6.0 , UL/cUL, CB, CE, ErP, FCC(Class B), CCC, BSMI, CU, C-Tick, VCCI, TCO6.0, TUV-GS, TUV-Ergo, ISO-9241-307, PSE, J-MOSS, Taiwan Green Mark(Option), HF(Option), RoHS, WEEE, Windows 7 and 8 WHQL, Mac Compliance, Ukraine, KC,	734.4x615x240 mm	734.4*431*66.85 mm	847*552 *350 mm	11.68 Kg	15.74 Kg			
PA329Q	Power Cord, DisplayPort-to-mini DisplayPort cable, HDMI cable, USB 3.0	Energy Star 7.0 , EPEAT Gold, UL/cUL, CB, CE, ErP, FCC(Class B), CCC, BSMI, CU, C-Tick, VCCI, TCO7.0, TUV-GS, TUV-Ergo, PSE, J-MOSS, Taiwan Green Mark(Option), HF(Option), RoHS, WEEE, Windows 7, 8.1/10 WHQL, Mac Compliance, Ukraine,	734.4x615x240 mm	734.4*431*66.85 mm	847*552 *350 mm	11.68 Kg	15.74 Kg			
PG348Q	120W Power adapter, Power cord, DisplayPort cable, HDMI cable, USB3.0 cable, Warranty Card, Quick start guide, Support CD, Giveaway ROG sticker	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, RCM, VCCI, PSE, CEL Level 2, J-MOSS, RoHS, WEEE, Windows 7/8.1/10 WHQL, KCC, E-STANDBY, PSE, TUV-Flicker Free, TUV-Low Blue Light	829 x 558 x 297 mm	829 x 323 x 109 mm	320 x 508 x 942 mm	11.1 kg	14.9 kg			
MX34VQ	HDMI cable, DP cable(optional), Power Cord, Warranty card, QSG	UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU, RCM,VCCI, J-MOSS, RoHS, MEPS, Windows 7 & 8.1 & 10,WHQL, KCC, E-Standby, WEEE, TUV – Flicker free, TUV – Low Blue Light	829 x 558 x 297 mm	N/A	320 x 508 x 942 mm	8.4Kg	13.5Kg			
MB169B+	Support CD, USB 3.0 Cable, Quick start guide, ASUS Smart Case	UL/cUL, CB, CE, CCC, FCC, BSMI, EAC, C-Tick, VCCI, RoHS, WEEE, Windows 7 &8 WHQL, PSE	379 x 236 x 8 mm	379 x 236 x 8 mm	435 x 297 x 57 mm	0.8kg	2.0kg			
MB16AC	USB Type-C cable, USB Type-C to A adapter, Quick start guide, ASUS smart case, ZenScreen pen	Energy Star®, UL/cUL, CB, CE, CCC, KCC, FCC, BSMI, EAC(CU), RCM, VCCI, J-Moss, UkrSEPRO, RoHS, WEEE, Windows 7 & 8.1 & 10 WHQL, TUV-Blue light filter, TUV-Flicker	359.7 x 226.4 x 8.0 mm	--	434 x 310 x 76 mm	0.8 kg	3.0kg	3780pcs	1800pcs	180pcs

Model	Price	Display Technology		Light Source	Light Source Life(max)	Native Resolution	Light Output(Max. lumens)	Contrast Ratio(typical)	Display Colors	Throw Ratio(@16:10)	Projection Distance	Projection/ Screen Size	Projection Offset	Zoom Ratio	Picture Modes	Keystone adjustment	Auto Keystone	Aspect Ratio	3D Ready
S1	$649.00	0.3" DLP®		LED	30,000 hours	WVGA 854x480	200 lumens (up to 70 Lumens with battery)	1000:1	16.7 M	1.1(41"@1m @16:9)	0.73 ~ 2.43 meters	30 ~ 100 inches	100%	Fixed	Standard/Theater/Presentation/Battery/Flashlight/SOS	–	–	Auto, 4:3, 16:9	–
B1MR	$1,159.00	0.45" DLP®		R/G/B LED	30,000 hours	WXGA 1280x800	900 Lumens	3500:1 DCR	1.07 Billions	0.9 (51" @1m)	0.6 ~ 3m	31.2~153 inches	105 ± 5 %	Fixed	7 Modes(Standard Mode / Black board / White board / Dynamic Mode /sRGB Mode / Scenery Mode / Theater Mode)	Digital (Up to ±40 degree)	Yes	16:10/ 16:9 /4:3	–
P3B	$1,199.00	0.45" DLP®		R/G/B LED	30,000 hours	WXGA 1280x800	800 Lumens(with AC) 500 Lumens @ 1.0hr (with battery) 150 Lumens @ 2 hrs (with battery)	1000:1	16.7 M	0.8 (58" @1m)(@16:10)	0.43 ~ 3.44m	25~200 inches	100 ± 5 %	Fixed	AC Mode: 5 Modes(Standard Mode/ Dynamic Mode /sRGB Mode / Scenery Mode / Theater Mode)	Digital (Up to ±40 degree)	Yes	16:10/ 16:9 /4:3	Yes
E1	$539.00	0.2" DLP®		LED	30,000 hours	WVGA 854x480	150 lumens (up to 150 Lumens with battery)	800:1	16.7 M	1.4 (31"@1m @16:9)	0.5 ~ 3.87 meters	15.5 ~ 120 inches	100%	Fixed	Standard/Theater/ Presentation/ECO/ Flashlight/SOS	Digital (Up to ± 40 degree)	Yes	Auto, 4:3, 16:9	--

Model	Projector Placement	Built-in Speakers	Analog Signal Frequency	Digital Signal Frequency	Power Consumption(Typical)	Power Standby mode	Internal Battery	Battery Life	Acoustic Noise	PC Signal Input	Video Input	Audio Output	Card Reader	USB 2.0 Port	LAN Control	Wireless Display
S1	Front table, Front Ceiling, Rear table, Rear Ceiling	Yes, 2W speaker (ASUS SonicMaster Audio technology)	–	24.7~74.6KHz(H)/ 50~60 Hz(V)	<32W	<0.5W	6000mAh (1A@5V)	22Wh	32 dB(Standard/ Theater Mode)/ 28 dB	HDMI/MHL	–	Earphone out	–	USB Port for Charge (1A@5V)	–	–
B1MR	Front Table, Front Ceiling, Rear Table, Rear Ceiling	Yes, 2W speaker*2 (ASUS SonicMaster Technology)	31.5 ~ 91.1 KHz(H)/ 50 ~85 Hz(V)	31.5 ~ 91.1 KHz(H)/ 50 ~ 85 Hz(V)	≤65W(Eco mode)/≤85W(Normal Mode)	< 0.5W	–	–	Normal mode: 32dBA, Typical, Eco mode: 28dBA, Typical Normal	D-sub, HDMI1.3(HDCP support)	Composite Video	Earphone out	Yes(1x SD card slot for multimedia playback)	Yes(1xType A, for Service FW upgrade and Media features of USB WiFi dongle, USB display, USB thumb disk)	–	Yes
P3B	Front Table, Front Ceiling, Rear Table, Rear Ceiling	Yes, 2W speaker(ASUS SonicMaster Audio technology)	(H):15.37~91.14 KHz (V):24~120Hz(120Hz for 3D feature)	(H):15.37~91.14 KHz (V):24~120Hz(120Hz for 3D feature)	<65W	< 0.5W	12000 mAh	44.28Wh(up to 3 hours)	32dBA(Standard mode), 28dBA (Theater mode)	D-sub, HDMI/MHL	–	Earphone out	Yes(1x MicroSD card slot, up to 32GB)	Yes(2xType A, Down: Service FW upgrade and power bank charger(5V/1.5A); Media features, up:USB thumb disk,	–	Yes (depond on different region)
E1	Front table, Front Ceiling, Rear table, Rear Ceiling	Yes, 2W speaker (ASUS SonicMaster Audio technology)	--	24.7~74.6K Hz(H)/ 50~60 Hz(V)	<=24W	<0.5W	6000mAh (1A@5V)	22Wh	30 dB(Standard Mode)/ 28 dB (Theater	HDMI/MHL	--	Earphone out	--	USB Port for Charge (1A@5V)	--	--

Model	Video	Audio	Picture	Document Viewer	Chassis Colors	Tripod Socket	Supporting Stand	On-machine	Lens cover	Kensington lock	Physical Dimension	Box Dimension	Net Weight (Esti.)	Gross Weight (Esti.)				
S1	–	–	–	–	Silver	Yes	–	Yes(Menu key,Navegation	Yes	–	110.5 x 30.7 x 102 mm	186 x 122 x 240mm	342g	1.82kg	5°C ~ 40°C	15~85% RH	HDMI cable, MHL cable,	
B1MR	MOV/MP4/AVI/MKV/MPG/MPEG/WMV/DIVX/TS/DAT/VOB/3GP/RM/RMVB	MP3/MP1/MP2/WMA/AAC/ADPCM-WAV/PCM-WAV/OGG	JPG/JPEG/BMP	PDF/DOC/DOCX/XLS/PPT/PPTX/TXT	Black	Yes	Yes (tilt angle: 5±1° and 9.5±1°)	Yes(MediaCenter, Input, Power Image position,	Yes	Yes	175(W)x 44.5(H)x 138(D) mm	338x225 x80mm	0.9kg	2.4kg	0 ~ 40 °C	20 ~ 90 %	bag, 90W Power adapter, Power cord, D-Sub	
P3B	MOV/MP4/AVI/MKV/MPG/MPEG/WMV/DIVX/TS/DAT/VOB/3GP/RM/RMVB	MP3/MP1/MP2/WMA/AAC/ADPCM-WAV/PCM-WAV/OGG	JPG/JPEG/BMP	PDF/DOC/DOCX/XLS/PPT/PPTX/TXT	White	Yes	Yes	Yes(MediaCenter, Input, Power Image position,	Yes	Yes	153.5(W) x 43(H)x 131.2(D) mm	295(W)*255(D)*80(H)mm	750g	1.87 kg	0 ~ 40 °C	20 ~ 90 %	carrying bag, power adapter, power cord,	
E1	--	--	--	--	--	Silver	Yes	--	Yes(Menu key,Navegation Keys)	Yes	--	83 x 29 x 110 mm	TBC	310g	880g	0°C ~ 40°C	20~90% RH	HDMI cable, , Power Adapter , AC	CB/ CE/ FCC/ VCCI / CU/

Bizgram Asia Pte Ltd 1 Rochor Canal Road, # 05-49/50
Simlim Square, Level 5, Outside the Central Lift. Singapore
188504.