



Bizgram Asia Pte Ltd
 Retail Wholesale Factory Outlet Address :
 #05-08 Sim Lim Square
 1 Rocher Canal Road
 Singapore 186504
 Tel : +65-63346455 / 63341373
 Fax : +65-63346415
 SMS / Whatsapp : +65 - 8889 9555 / 8777 6955



Please send whatsapp to check stocks and timing, and any other details before visiting the store. As stocks situation might vary and price is for reference only and might change anytime due to any situation.

| | WORKSTATION P10S WS | WORKSTATION WS X299 ACE | WORKSTATION WS X299 SAGE | WORKSTATION WS X299 SAGE/10G | WORKSTATION PRO WS C246-ACE | WORKSTATION WS C621E SAGE | WORKSTATION WS C422 PRO/SE | WORKSTATION WS C422 SAGE/10G | WORKSTATION Z10PE-D8 WS | WORKSTATION Z10PE-D16 WS | |
|--------------------------|---|--|--|--|--|---|--|---|---|---|---|
| Socket | LGA 1151 | Socket LGA 1200 | Socket LGA 2066 | Socket LGA 2066 | Socket LGA 1151 | Socket LGA 3647 * 2 | Socket LGA 2066 | Socket LGA 2066 | Socket LGA 2066 | Socket LGA 2011-v3 * 2 | Socket LGA 2011-v3 * 2 |
| CPU | Build in Intel® Socket 1151 Core™ i7/Core™ i5/Core™ i3/for Xeon® E3-1200 v5 and 6th generation Core™ Pentium® and Celeron® Processors | Intel® Socket 1200 for 10th Gen Intel® Xeon® Core™ Processors | Intel® Socket 2066 Core™ X-Series | Intel® Socket 2066 Core™ X-Series | Intel® Socket 1151 For Xeon® E-2200/E-2100 family 5th / 6th Gen Intel® Core™ / Pentium® and Celeron® Processors | Intel® Xeon® Scalable Processors Family (20W) | Intel® Socket 2066 Processors | Intel® Socket 2066 Processors | Intel® Socket 2066 Processors | Intel® Socket 2011-v3 for Intel® Xeon® processor | Intel® Socket 2011-v3 for Intel® Xeon® processor |
| Chipset | Intel® C236 | Intel® W480 | Intel® X299 | Intel® X299 | Intel® C246 | Intel® C621 | Intel® C422 | Intel® C422 | Intel® C612 PCH | Intel® C612 PCH | |
| Memory | 4 x DIMM, Max. 32GB, DDR3 1600/1333 MHz ECC, Non-ECC, Un-buffered Memory | 4 x DIMM, Max. 128GB, DDR4 4800(O.C.)/4600(O.C.)/4500(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/3866(O.C.)/3666(O.C.)/3400(O.C.)/3200(O.C.)/3000(O.C.)/2933(O.C.)/2800(O.C.)/2666/2400/2133 MHz Non-ECC, Un-buffered Memory | Intel® Core™ X-series Processors (8-core above) | Intel® Core™ X-series Processors (8-core above) | 4 x DIMM, Max. 128GB, DDR4 2666/2400/2133 MHz ECC and non-ECC Memory | 12 x DIMM, Max. 768GB, DDR4 2666/2400 MHz RDIMM, LR-DIMM Memory | 8 x DIMM, Max. 512GB, DDR4 2666/2400/2133 MHz RDIMM, LR-DIMM Memory *1 | 8 x DIMM, Max. 512GB, DDR4 2666/2400/2133 MHz RDIMM, LR-DIMM Memory *1 | 8 x DIMM, Max. 512GB, DDR4 2666/2400/2133 MHz RDIMM, LR-DIMM Memory | 16 x DIMM, Max. 512GB, DDR4 2133/1866/1600/1333 MHz RDIMM, LR-DIMM, NVDIMM Memory | 16 x DIMM, Max. 512GB, DDR4 2133/1866/1600/1333 MHz RDIMM, LR-DIMM, NVDIMM Memory |
| Graphic | Intel® DVI / DisplayPort ports | Intel® DisplayPort ports | Multi-GPU Support | Multi-GPU Support | Intel® DisplayPort ports | Multi-GPU Support | Multi-GPU Support | Multi-GPU Support | Multi-GPU Support | Multi-GPU Support | |
| Multi-GPU Support | Supports AMD Quad-GPU CrossFireX™ Technology | Supports AMD 3-Way CrossFireX™ Technology | Supports NVIDIA® 4-Way SLI™ Technology | Supports NVIDIA® 4-Way SLI™ Technology | Supports AMD 2-Way CrossFireX™ Technology | NVIDIA® 4-Way SLI™ Technology | NVIDIA® 3-Way SLI™ Technology | NVIDIA® 3-Way SLI™ Technology | Supports NVIDIA® 4-Way SLI™ Technology | Supports NVIDIA® 4-Way SLI™ Technology | |
| Expansion Slots | 1 x PCIe 3.0/2.0 x16 (x16/x8) 1 x PCIe 3.0/2.0 x16 (x8 mode) *1 1 x PCIe 3.0/2.0 x16 (x4 mode) *2 1 x PCIe 3.0/2.0 x16 (x4 mode) *2 | 2 x PCIe 3.0 x16 (x16 or dual x8) 1 x PCIe 3.0 x16 (x4 mode) 2 x PCIe 3.0 x1 | 7 x PCIe 3.0/2.0 | 7 x PCIe 3.0/2.0 | 3 x PCIe 3.0/2.0 x16 (x16 or dual x8) 1 x PCIe 3.0/2.0 x16 (max at x8 mode) 2 x PCIe 3.0/2.0 x1 | 3 x PCIe 3.0/2.0 x16 (x16 mode) 2 x PCIe 3.0/2.0 x16 (Single at x16, dual at x8/x8) 2 x PCIe 3.0/2.0 x16 (x8 mode) | 7 x PCIe 3.0/2.0 | 7 x PCIe 3.0/2.0 | 7 x PCIe 3.0/2.0 | 4 x PCIe 3.0/2.0 x16 (x16 mode) *3 2 x PCIe 3.0/2.0 x16 (x8 mode) *3 | 4 x PCIe 3.0/2.0 x16 (x16 mode) *3 2 x PCIe 3.0/2.0 x16 (x8 mode) *3 |
| Storage | Intel® C236 Chipset: 8 x SATA 6Gb/s ports) 2 x M.2 Socket 3 Support Raid 0, 1, 5, 10 | Intel® W480 Chipset: 4 x SATA 6Gb/s ports) 2 x M.2 Socket 3 Support Raid 0, 1, 5, 10 | Intel® X299 Chipset: 1 x M.2 Socket 3 1 x M.2 Socket 3 8 x SATA 6Gb/s ports) 2 x U.2 connector*1 Support Raid 0, 1, 5, 10 | Intel® X299 Chipset: 1 x M.2 Socket 3 1 x M.2 Socket 3 8 x SATA 6Gb/s ports) 1 x U.2 connector*1 Support Raid 0, 1, 5, 10 | Intel® C246 Chipset: 1 x M.2 Socket 3 8 x SATA 6Gb/s ports) 1 x U.2 connector*1 Support Raid 0, 1, 5, 10 | Intel® C621 Chipset: 8 x SATA 6Gb/s ports), Support Raid 0, 1, 5, 10 ASMedia® SATA 6Gb/s controller: 2 x SATA 6Gb/s ports), 4 x U.2 connector, 1 x M.2 Socket 3 | Intel® C422 chipset: 1 x M.2 Socket 3 2 x U.2 connector 8 x SATA 6Gb/s ports) Support Raid 0, 1, 5, 10 1 x M.2 x4 Socket 3*2, 1 x M.2 x4 Socket 3*3, 1 x M.2 x4 Socket 3*3, | Intel® C422 chipset: 2 x U.2 connector 8 x SATA 6Gb/s ports) Support Raid 0, 1, 5, 10 1 x M.2 x4 Socket 3*2, 1 x M.2 x4 Socket 3*3, | Intel® C612 chipset: 4 x SATA 6Gb/s ports), gray, 4 x SATA 6Gb/s ports), black 1 x SATA Express port, gray 1 x M.2 Socket 3 Support Raid 0, 1, 5, 10 ASMedia® SATA Express controller: 2 x SATA 6.0 Gb/s ports | Intel® C612 chipset: 10 x SATA 6Gb/s ports), gray, *4 1 x M.2 Socket 3, black, *5 Support Raid 0, 1, 5, 10 | |
| LAN | Intel® I210, 2 x Gigabit LAN | Intel® I225-LM 2.5Gb Ethernet Realtek® RTL8117 | Intel® I210-AT, 1 x Gigabit LAN Intel® I219-LM, 1 x Gigabit LAN | Intel® X550-AT2, 2 x 10 Gigabit LAN Controller | Intel® I210-AT Intel® I219-LM | Intel® I210-AT, 2 x Gigabit LAN | Intel® I210-AT, 2 x Gigabit LAN | Intel® X550-AT2 2 x 10 Gigabit LAN | Intel® I210-AT, 2 x Gigabit LAN | Intel® I210-AT, 2 x Gigabit LAN | |
| Audio | Realtek® ALC1150 8-Channel High Definition Audio CODEC | Realtek® ALC S1220A 8-Channel High Definition Audio CODEC | Realtek® ALC S1220A 7.1-Channel High Definition Audio CODEC | Realtek® ALC S1220A 7.1-Channel High Definition Audio CODEC | Realtek® ALC S1220A 8-Channel High Definition Audio CODEC | Realtek® S1220A 7.1-Channel High Definition Audio CODEC | Realtek® ALC S1220A 8-Channel High Definition Audio CODEC | Realtek® ALC S1220A 7.1-Channel High Definition Audio CODEC | Realtek® ALC1150 8-Channel High Definition Audio CODEC | Realtek® ALC1150 8-Channel High Definition Audio CODEC | |
| IEEE 1394 | NA | IEEE 1394 | IEEE 1394 | IEEE 1394 | IEEE 1394 | IEEE 1394 | IEEE 1394 | IEEE 1394 | IEEE 1394 | IEEE 1394 | |
| USB Ports | Built-in Controller: 4 x USB 2.0 port(s) (Type-A, 4 at mid-board) 6 x USB 3.0 port(s) (4 at back panel, 2 at mid-board) 2 x USB 3.1 Gen 1 port(s) (2 at back panel, Type-A + Type-C) | USB Ports 4 x USB 2.0 port(s) 8 x USB 3.1 Gen 1 port 4 x USB 2.0 port(s) | USB Ports 8 x USB 3.1 Gen 1 port 4 x USB 2.0 port(s) | USB Ports 8 x USB 3.1 Gen 1 port 4 x USB 2.0 port(s) | USB Ports 4 x USB 2.0 port(s) (4 at mid-board) | USB Ports Intel® C621 Chipset: 8 x USB 3.1 Gen 1 port(s) (4 at back panel, 4 at mid-board) 4 x USB 2.0 port(s) (2 at back panel, 2 at mid-board) | USB Ports Intel® C422 Chipset: 8 x USB 3.1 Gen 1 port(s) (4 at back panel, 2 at mid-board) 6 x USB 2.0 port(s) (4 at back panel, 2 at mid-board) | USB Ports Intel® C422 Chipset: 8 x USB 3.1 Gen 1 port(s) (4 at back panel, 2 at mid-board) 6 x USB 2.0 port(s) (4 at back panel, 2 at mid-board) | USB Ports Intel® C612 Chipset: 4 x USB 3.0/2.0 port(s) (4 at back panel, 2 at mid-board) 4 x USB 2.0/1.1 port(s) (2 at back panel, 2 at mid-board) | USB Ports Intel® C612 Chipset: 6 x USB 3.0/2.0 port(s) (4 at back panel, 2 at mid-board) 6 x USB 2.0/1.1 port(s) (4 at back panel, 2 at mid-board) | |
| Form Factor | ATX Form Factor 12 inch x 9.6 inch | Form Factor CEB Form Factor 12 inch x 9.6 inch | Form Factor CEB Form Factor 12 inch x 10.5 inch | Form Factor CEB Form Factor 12 inch x 10.5 inch | Form Factor ATX Form Factor 12 inch x 9.6 inch | Form Factor EEB Form Factor 12 inch x 9.6 inch | Form Factor ATX Form Factor 12 inch x 10.5 inch | Form Factor CEB Form Factor 12 inch x 10.5 inch | Form Factor EEB Form Factor 12 inch x 13 inch | Form Factor EEB Form Factor 12 inch x 13 inch | |

SPECIFICATIONS