

Axis Communications

Bizgram Asia Pte Ltd
 #05-50 Sim Lim Square
 1 Rochor Canal Road
 Singapore 188504
 Open Daily 10am to 8pm
 No Lunch Break – 7 Days a week
 Open on Public Holidays
 ROC : 200903547Z
 GST : 200903547Z
 UEN : 200903547Z
 Gebiz : 200903547Z

 Whatsapp : +65-87776955
 SMS : +65-87776955
 Tel : +65-63346455
 Fax : +65-63341615
 Email : sales @ bizgram.com

Product Name	Minimum order quantity	High volume order	Status	Product Number UK	Product Number AUS	Product Number EUR	Product Description	Price
Explosion Protected XF40-Q1765 ATEX IECEX	1	2	Built to order	0835-001	0835-001	0835-001	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,209
XF40-Q1765 -60C ATEX IECEX	1	1	Built to order	0835-011	0835-011	0835-011	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,827
XF40-Q1765 INMETRO	1	1	Built to order			0835-021	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to INMETRO. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,209
XF40-Q1765 -60C INMETRO	1	1	Built to order			0835-031	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to INMETRO. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,827

XF40-Q1765 CSA	1	1	Built to order	0835-041			Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CSA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,209
XF40-Q1765 -60C CSA	1	1	Built to order	0835-051			Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CSA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR- dynamic contrast. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,827
XF40-Q1765 CCOE	1	1	Built to order	0835-081	0835-081	0835-081	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CCOE. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,209
XF40-Q1765 -60C CCOE	1	1	Built to order	0835-091	0835-091	0835-091	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CCOE. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR- dynamic contrast. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,827
XF40-Q1765 CNEX	1	1	Built to order	0835-101			Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CNEX. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,209

XF40-Q1765 -60C CNEX	1	1	Built to order	0835-111			Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CNEX. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps.It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (- 76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,827
XF40-Q1765 IA	1	1	Name changed Built to order	0835-121		0835-121	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to IA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif,WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (- 40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,209
XF40-Q1765 -60C IA	1	1	Name changed Built to order	0835-131		0835-131	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to IA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (- 76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,827
XF40-Q1765 -50C UL	1	5	Built to order				Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to UL. Certification part code Oxalis-UL1410-15. Oxalis explosion-protected housing with three 3/4" NPT cable entries, Axis 1080p HDTV camera inside with 18x optical zoom , auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	8,136
XF60-Q1765 -50C 110V UL	1	20	Built to order				Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to UL. Certification part code Oxalis-UL2410-02. Oxalis explosion-protected housing with three 3/4" NPT cable entries, Axis 1080p HDTV camera inside with 18x optical zoom , auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps.It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 110V AC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	8,651

XF40-Q1765 EAC	1	1	Built to order			01485-001	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to EAC TR CU. Model XF40 Serie 1410, certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,209
XF40-Q1765 -60C EAC	1	1	Built to order			01486-001	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to EAC TR CU. Model XF40 Serie 1410, certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7,827
XP40-Q1765 -50C UL	1	1	Built to order				Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to UL. Certification part code Oxalis-UL1410-25/UL2420-01. Oxalis explosion-protected housing with 3/4" NPT cable entries, Axis 1080p HDTV camera inside with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	21,320
XP40-Q1765 -50C 110V UL	1	1	Built to order				Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to UL. Certification part code Oxalis-UL1410-25/UL2420-01. Oxalis explosion-protected housing with 3/4" NPT cable entries, Axis 1080p HDTV camera inside with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67 rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 110VAC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	21,629
XP40-Q1765 ATEX IECEx	1	1	Built to order	0836-001	0836-001	0836-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to ATEX and IECEx. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18,024

XP40-Q1765 -60C ATEX IECEX	1	1	Built to order	0836-011	0836-011	0836-011	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,054
XP40-Q1765 INMETRO	1	1	Built to order			0836-021	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to INMETRO. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18,024
XP40-Q1765 -60C INMETRO	1	1	Built to order			0836-031	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to INMETRO. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,054
XP40-Q1765 CSA	1	1	Built to order	0836-041			Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CSA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18,024
XP40-Q1765 -60C CSA	1	1	Built to order	0836-051			Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CSA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,054

XP40-Q1765 CCOE	1	1	Built to order	0836-081	0836-081	0836-081	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CCOE. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18,024
XP40-Q1765 -60C CCOE	1	1	Built to order	0836-091	0836-091	0836-091	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CCOE. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,054
XP40-Q1765 CNEK	1	1	Built to order	0836-101			Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CNEK. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR-dynamic contrast. Video motion detection and active tampering alarm. IP66 and IP67 rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield.	18,024
XP40-Q1765 -60C CNEK	1	1	Built to order	0836-111			Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CNEK. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,054
XP40-Q1765 IA	1	1	Name changed Built to order	0836-121		0836-121	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to IA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18,024

XP40-Q1765 -60C IA	1	1	Name changed Built to order	0836-131		0836-131	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to IA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,054
XP40-Q1765 EAC	1	1	Built to order			01487-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to EAC TR CU. Model XP40, Serie 2420, certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18,024
XP40-Q1765 -60C EAC	1	1	Built to order			01488-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to EAC TR CU. Model XP40, Serie 2420, certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,054
XF60-Q2901 UL 8.3FPS 19MM -50C 110V	1	1	Built to order				Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to UL. Certification part code OXALIS-UL2419-TL50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three 3/4" NPT cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG: simultaneous, individually configured streams in max. resolution at 8.3 fps. It supports ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 110 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	22,453

XF40-Q2901 UL 8.3FPS 19MM -50C	1	20	Built to order				Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to UL. Certification part code OXALIS-UL1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three 3/4" NPT cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG; simultaneous, individually configured streams in max. resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	21,629
XF40-Q2901 ATEX IECEx 8.3FPS 19MM -40C	1	1	Built to order	01089-001	01089-001	01089-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to ATEX and IECEx. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,569
XF40-Q2901 ATEX IECEx 8.3FPS 19MM -60C	1	1	Built to order	01090-001	01090-001	01090-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to ATEX and IECEx. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	20,187

XF40-Q2901 EAC 8.3FPS 19MM -40C	1	20	Built to order			01093-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to EAC. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,569
XF40-Q2901 EAC 8.3FPS 19MM -60C	1	20	Built to order			01129-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to EAC. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	20,187
XF40-Q2901 CSA 8.3FPS 19MM -40C	1	20	Built to order	01092-001			Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to CSA. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,569

XF40-Q2901 CSA 8.3FPS 19MM -60C	1	20	Built to order	01128-001			Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to CSA. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	20,187
XF40-Q2901 INMETRO 8.3FPS 19MM -40C	1	20	Built to order			01091-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to INMETRO. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19,569
XF40-Q2901 INMETRO 8.3FPS 19MM -60C	1	20	Built to order			01127-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to INMETRO. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	20,187

XP40-Q1942 UL 8.3FPS 19MM -50C	1	20	Built to order					Explosion-protected 316L stainless steel PT Thermal Network camera certified for hazardous areas according to UL. Certification part code UL1410-10-TI-50/UL2420-01. Oxalis explosion-protected housing with two 3/4" NPT cable entries and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG: simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	30,384
XP40-Q1942 UL 8.3FPS 19MM -50C 110V	1	20	Built to order					Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to UL. Certification part code OXALIS-UL2410-TI-50. Oxalis explosion-protected housing with two 3/4" NPT cable entries and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG: simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 110 V AC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	30,899
XP40-Q1942 ATEX IECEx 8.3FPS 19MM -40C	1	20	Built to order	01098-001	01098-001	01098-001		Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to ATEX and IECEx. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	25,749
XP40-Q1942 ATEX IECEx 8.3FPS 19MM -60C	1	1	Built to order	01099-001	01099-001	01099-001		Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to ATEX and IECEx. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	26,779
XP40-Q1942 EAC 8.3FPS 19MM -40C	1	20	Built to order			01102-001		Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to EAC. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	25,749

XP40-Q1942 EAC 8.3FPS 19MM -60C	1	20	Built to order			01138-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to EAC. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	26,779
XP40-Q1942 CSA 8.3FPS 19MM -40C	1	20	Built to order	01101-001			Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to CSA. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	25,749
XP40-Q1942 CSA 8.3FPS 19MM -60C	1	20	Built to order	01137-001			Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to CSA. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	26,779
XP40-Q1942 INMETRO 8.3FPS 19MM -40C	1	20	Built to order			01100-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to INMETRO. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	25,749
XP40-Q1942 INMETRO 8.3FPS 19MM -60C	1	20	Built to order			01136-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to INMETRO. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	26,779

D201-S XPT Q6055	1	10	Built to order	01480-001	01480-001	01480-001	Explosion-protected, top performance, PoE powered HDTV 1080p PTZ dome network camera with 32x zoom, FM listed for hazardous locations Class I Division 1, Groups B, C, D, T6; Class 1 Zone 1 IIB + H2 T6, -20°C ≤ Ta ≤ +55°C (FM17US0156). Stainless Steel 316L housing. Auto day/night functionality, Zipstream, wide dynamic range, electronic image stabilization, highlight compensation. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p@30 fps, 720@60 fps. High PoE midspan with fiber slot is included (for installation in safe area or Ex d enclosure), AXIS Surveillance SD Card 64GB. Optional accessories: Wall and pole mount. Built to order, 6 weeks lead time.	15,449
F101-A XF P1367	1	2	Built to order	01703-001	01703-001	01703-001	Explosion-protected, PoE powered, 5 MP fixed network camera, FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T6; Class 1 Zone 1 IIB + H2 AEx d IIB+H2 T6, Class II Zone 21, AEx d IIIC T6 Db, -20°C ≤ Ta ≤ +60°C. Powder coated aluminum housing (RAL 3017). i-CS mount lens, 2.8 - 8mm, F1.2. Lightfinder, Zipstream, WDR - forensic capture. AXIS Surveillance SD Card 64GB, sunshield included. Built to order, 6 weeks lead time.	4,119
EXCAM XPT Q6055	1	7	Built to order	01520-001	01520-001	01520-001	Explosion-protected, top performance, PoE powered HDTV 1080p PTZ dome network camera with 32x zoom, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T6 Gb, Ex II 2 D Ex t IIIC T80°C Db IP68, -50°C ≤ Ta ≤ +60°C. Model key:T08-TNXCD-C-005-K-LL. Stainless Steel 316L housing. Auto day/night functionality, Zipstream, wide dynamic range, electronic image stabilization, highlight compensation. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p@30 fps, 720@60 fps. AXIS T8154 PoE midspan with fiber slot is included (for installation in safe area or Ex d enclosure), AXIS Surveillance SD Card 64GB, EXTB-3 connection box, 5m network and power cable preinstalled. Built to order, 6 weeks lead time.	15,449
EXCAM XF Q1785	1	15	Built to order	01572-001	01572-001	01572-001	Explosion-protected, PoE powered, HDTV 1080p 32x optical zoom, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T5 Gb, Ex II 2 D Ex t IIIC T95°C Db IP68, -60°C ≤ Ta ≤ +60°C. Model key:T08-VA2.3.K3.BOR5-C-005-K-LL. Stainless Steel 316L housing with wiper and sunshield. Lightfinder, Zipstream, forensic WDR, electronic image stabilization. AXIS Surveillance SD Card 64GB, 5m network and power cable preinstalled, Ex e connection box. Built to order, 6 weeks lead time.	10,299
EXCAM XF Q1645	1	7	Built to order	01562-001	01562-001	01562-001	Explosion-protected, PoE powered, HDTV 1080p fixed network camera, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T5 Gb, Ex II 2 D Ex t IIIC T100°C Db IP68, -60°C ≤ Ta ≤ +60°C. Model key:T08-VA2.3.K1.BOR2-C-005-K-LL. Stainless Steel 316L housing with sunshield. 3.9 - 10mm F1.5 i-CS lens. Lightfinder, Zipstream, forensic WDR, electronic image stabilization, AXIS Motion Guard, AXIS Fence Guard, AXIS Surveillance SD Card 64GB, 5m network and power cable preinstalled, Ex e connection box. Built to order, 6 weeks lead time.	8,754
EXCAM XF P1367	1	10	Built to order	01720-001	01720-001	01720-001	Explosion-protected, PoE powered, 5 MP fixed network camera, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T5 Gb, Ex II 2 D Ex t IIIC T100°C Db IP68, -60°C ≤ Ta ≤ +60°C. Model key:T08-VA2.3.K3.BOR2-C-005-K-LL. Stainless Steel 316L housing. 2.8 - 8.5mm F1.2 i-CS lens. Lightfinder, Zipstream, forensic WDR. AXIS Surveillance SD Card 64GB, 5m network and power cable preinstalled. Built to order, 6 weeks lead time.	7,209
F101-A XF Q1785	1	6	Built to order	01587-001	01587-001	01587-001	Explosion-protected, PoE powered, HDTV 1080p 32x optical zoom, FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T6; Class 1 Zone 1 IIB + H2 AEx d IIB+H2 T6, Class II Zone 21, AEx d IIIC T6 Db, ATEX/IECEX, -40°C ≤ Ta ≤ +60°C. Powder coated aluminum housing (RAL 3017). Lightfinder, Zipstream, forensic WDR, electronic image stabilization. AXIS Surveillance SD Card 64GB. Built to order, 6 weeks lead time.	5,149

D101-A XF P3807	1	5	Built to order	01914-001	01914-001	01914-001	D101-A XF P3807 is an explosion-protected multi-sensor camera, providing an easy, reliable and cost-efficient one-camera installation – reducing installation time, cabling and VMS license costs. Thanks to its excellent image sensors, along with Forensic WDR and Lightfinder technology, it provides great video quality in any light conditions. Its four sensors give a seamless 180° panoramic overview, at up to 30 fps in 8 MP resolution. Enclosed in a red aluminum housing and FM listed for hazardous locations Class I/II Division 1, Groups B, C, D, E, F, G, T6; Class 1 Zone 1 IIB + H2 T6, -20°C ≤ Ta ≤ +55°C (FM17US0156). ATEX, IECEx II 2G Ex db IIB + H2, T6 GB, II 2 D Ex tb IIIC T85°C Db IP66.	10,299
Fixed Box								
AXIS M1045-LW	1	100		0812-003	0812-006	0812-002	Small, wireless indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes wall, corner bracket and table top bracket for easy mounting. Power supply included.	236
AXIS M1065-L	1	200		0811-001	0811-001	0811-001	Small, full-featured indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Built-in microphone and mini-speaker, integrated PIR motion sensor. Powered over Ethernet (PoE) or by accessory power supply. Includes wall, corner bracket and table top bracket for easy mounting. Power supply not included.	287
AXIS M1065-LW	1	500		0810-003	0810-006	0810-002	Small, full-featured wireless indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Built-in microphone and mini-speaker, integrated PIR motion sensor. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes wall, corner bracket and table top bracket for easy mounting. Power supply included.	308
AXIS M1124	1	100		0747-001	0747-001	0747-001	HDTV 720p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Includes stand. Power supply not included.	359
AXIS M1124 BULK 10PCS	1	1		0747-021	0747-021	0747-021	AXIS M1124 in 10-pack. Cannot be sold separately as single packs.	3,552
AXIS M1124 BAREBONE	1	1		0747-031	0747-031	0747-031	AXIS M1124 Barebone. No lens.	339

AXIS M1124-E	1	15		0748-001	0748-001	0748-001	Outdoor, NEMA 4X, IP66 and IK10-rated, lightweight, HDTV 720p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Operation in -20°C to +50°C. Powered by IEEE 802.3af midspan. Includes a wall bracket, Torx T20 screw driver and IP66-rated cable glands. Midspan not included.	462
AXIS M1125	1	100		0749-001	0749-001	0749-001	HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Includes stand. Power supply not included.	432
AXIS M1125 BULK 10PCS	1	1		0749-021	0749-021	0749-021	AXIS M1125 in 10-pack. Cannot be sold separately as single packs.	4,273
AXIS M1125 BAREBONE	1	6		0749-031	0749-031	0749-031	AXIS M1125 Barebone. No lens.	411
AXIS M1125-E	1	60		0750-001	0750-001	0750-001	Outdoor, NEMA 4X, IP66 and IK10-rated, lightweight, HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Operation in -20°C to +50°C. Powered by IEEE 802.3af midspan. Includes a wall bracket, Torx T20 screw driver and IP66-rated cable glands. Midspan not included.	535
AXIS M1134	1	20	New	01979-001	01979-001	01979-001	HDTV 720p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 720p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 2 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	359
AXIS M1134 BAREBONE	1	20	New	01979-041	01979-041	01979-041	AXIS M1134 Barebone in single pack. No lens. No power supply	339
AXIS M1135	1	20	New	01768-001	01768-001	01768-001	HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 2 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	432
AXIS M1135 BAREBONE	1	20	New	01768-041	01768-041	01768-041	AXIS M1135 Barebone in single pack. No lens. No power supply.	411

AXIS M1135-E	1	20	New	01772-001	01772-001	01772-001	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -25°C to +50°C. PoE class 2 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66-rated cable glands. Midspan or power supply not included.	535
AXIS M1137	1	20	New	01769-001	01769-001	01769-001	5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	514
AXIS M1137 BAREBONE	1	20	New	01769-041	01769-041	01769-041	AXIS M1137 Barebone in single pack. No lens. No power supply	493
AXIS M1137-E	1	20	New	01773-001	01773-001	01773-001	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight 5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -25°C to +50°C. PoE class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66-rated cable glands. Midspan or power supply not included.	617
AXIS M1145-L	1	70		0591-001	0591-001	0591-001	HDTV camera for day and night surveillance with varifocal 3-10.5mm P-iris lens. Remote 3.5 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p or 2MP resolution at 30 fps. Video motion detection and active tampering alarm and I/O ports. Optimized IR, a power-efficient LED technology that provides an adaptable angle of IR illumination up to 15 meters (50 feet) MicroSD/SDHC memory card slot for edge storage. Includes stand for easy mounting. Power over Ethernet. Midspan not included.	514
AXIS M1145-L BULK 10PCS	1	1		0591-021	0591-021	0591-021	AXIS M1145-L in 10-pack/bulk. Cannot be sold separately as single packs.	5,097
AXIS M2025-LE	1	350		0911-001	0911-001	0911-001	Day/night, compact and outdoor-ready bullet style HDTV camera, IP66- and IK08-rated. Built-in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	339

AXIS M2025-LE BLACK	1	40		0988-001	0988-001	0988-001	Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66- and IK08-rated Built-in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	339
AXIS M2025-LE BULK 10PCS	1	1		0911-021	0911-021	0911-021	AXIS M2025-LE in 10-pack/bulk. Cannot be sold separately as single packs.	3,346
AXIS M2026-LE MK II	1	125		01049-001	01049-001	01049-001	Day/night, compact and outdoor-ready bullet style HDTV camera, IP66- and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264/H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	411
AXIS M2026-LE MK II BLACK	1	60		01050-001	01050-001	01050-001	Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66- and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264/H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	411
AXIS M2026-LE MK II BULK 10PCS	1	1		01049-021	01049-021	01049-021	AXIS M2026-LE Mk II in 10-pack/bulk. Cannot be sold separately as single packs.	4,067
AXIS M2026-LE MK II BLACK BULK 10PCS	1	1		01050-021	01050-021	01050-021	AXIS M2026-LE Mk II Black in 10-pack/bulk. Cannot be sold separately as single packs.	4,067
AXIS P1214	1	20		0532-001	0532-001	0532-001	Miniature HDTV pinhole camera for discreet surveillance. Cable from sensor unit going in the direction of the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	514
AXIS P1214 BULK 10 PCS	1	1		0532-021	0532-021	0532-021	AXIS P1214 in pack of 10 units	5,097
AXIS P1214-E	1	50		0533-001	0533-001	0533-001	Miniature HDTV camera for discreet outdoor surveillance. Cable from sensor unit going in the direction of the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	514
AXIS P1214-E BULK 10 PCS	1	6		0533-021	0533-021	0533-021	AXIS P1214-E in pack of 10 units	5,097
AXIS P1224-E	1	125		0654-001	0654-001	0654-001	Miniature HDTV camera for discreet indoor/outdoor surveillance with 145° horizontal field of view. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	514
AXIS P1244	1	40		0896-001	0896-001	0896-001	AXIS P1244 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Sensor Unit. The camera provides HDTV 720p resolution and 102° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Comes with a kit for flush mount installation in ceiling/wall.	308

AXIS P1245	1	100		0926-001	0926-001	0926-001	AXIS P1245 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS FA1105 Sensor Unit. The camera provides HDTV 1080p resolution, 111° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance. Comes with a kit for flush mount installation in ceiling/wall.	349
AXIS P1254	1	20		0924-001	0924-001	0924-001	AXIS P1254 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Bullet Sensor Unit that enables easy mounting on walls or ceilings and with the ability to tilt and rotate. The camera provides HDTV 720p resolution and 102° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance.	308
AXIS P1264	1	125		0925-001	0925-001	0925-001	AXIS P1264 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Pinhole Sensor Unit that is designed for extremely discreet indoor installations. The camera provides HDTV 720p resolution and 57° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Bracket included for mounting behind thin metal, plastic or glass panel.	308
AXIS P1265	1	90		0927-001	0927-001	0927-001	AXIS P1265 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and an AXIS FA1125 Pinhole Sensor Unit that is designed for extremely discreet indoor installations. The camera provides HDTV 1080p resolution, 91° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Bracket included for mounting behind a thin metal, plastic or glass panel.	359
AXIS P1275	1	6		0928-001	0928-001	0928-001	AXIS P1275 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and an AXIS FA4115 Dome Sensor Unit with a varifocal lens that enables easy mounting on walls or ceilings. It can be manually directed with pan, tilt and rotate movements. The camera provides HDTV 1080p resolution, 53-99° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance.	390

AXIS P1280-E 4MM 8.3 FPS	1	5		0940-001	0940-001	0940-001	<p>AXIS P1280-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/39.4ft cable. The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The flexible form factor allows it to be placed in locations with limited space and a wide range of mounting accessories enables wall, ceiling and recessed installations. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	823
AXIS P1290-E 4 MM 8.3 FPS	1	5		01168-001	01168-001	01168-001	<p>AXIS P1290-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/39.4ft cable and dome casing. The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	874
AXIS P1365 Mk II	1	200	Discontinued - contact Order dept for availability	0897-001	0897-001	0897-001	<p>HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 2.8-8 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 60 fps. WDR - Forensic Capture, Lightfinder and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Power over Ethernet. Includes stand with cable management. Power supply not included.</p>	771
AXIS P1365-E Mk II	1	200	Discontinued - contact Order dept for availability	0898-001	0898-001	0898-001	<p>Outdoor, NEMA 4X, IP66/67 and IK10-rated, lightweight, HDTV 1080p, day/night, fixed network camera with CS-mount varifocal 2.8-8 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 60 fps. WDR - Forensic Capture, Lightfinder and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Operation in -40°C to +50°C. Powered by IEEE 802.3af midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan not included.</p>	1,029
AXIS P1365 Mk II BULK 10PCS	1	8	Discontinued - contact Order dept for availability	0897-021	0897-021	0897-021	<p>AXIS P1365 Mk II in 10-pack. Cannot be sold separately as single packs. No power supplies.</p>	7,621

AXIS P1365 Mk II BAREB	1	15	Discontinued - contact Order dept for availability	0897-041	0897-041	0897-041	AXIS P1365 Mk II Barebone. No lens. No power supply.	668
AXIS P1365 Mk II BAREB BULK 10PCS	1	2	Discontinued - contact Order dept for availability	0897-051	0897-051	0897-051	AXIS P1365 Mk II Barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	6,684
AXIS P1375	1	250		01532-001	01532-001	01532-001	HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0 technology. Includes an IR corrected varifocal 2.8-10 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	668
AXIS P1375 BAREBONE	1	1		01532-031	01532-031	01532-031	AXIS P1375 Barebone in single pack. No lens. No power supply.	617
AXIS P1375-E	1	150		01533-001	01533-001	01533-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0 technology. Includes an IR corrected varifocal 2.8-10 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. Support for optional AXIS Fixed Box IR Illuminator Kit A and AXIS P13 Weathershield Extension A. Serial port for RS422/485 communication. Operation in -40°C to +60°C. Power over Ethernet or 12-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included.	926
AXIS P1375-E BAREBONE	1	1		01533-031	01533-031	01533-031	AXIS P1375-E Barebone. No lens. Midspan not included	874
AXIS P1367	1	30		0762-001	0762-001	0762-001	SMP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology for demanding light conditions. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens and remote back focus (camera also supports i-CS and DC-iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 8-28 V DC input. Includes black metal stand with hole for easy cable management. Midspan not included.	823
AXIS P1367 BAREBONE	1	2		0762-031	0762-031	0762-031	AXIS P1367 Barebone. No lens. No power supply.	720

AXIS P1367-E	1	150		0763-001	0763-001	0763-001	Outdoor, 5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder for demanding light conditions. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens and remote back focus (camera also supports i-CS and DC-iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS422/485 communication. Corridor format. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +55°C and intermittent up to +60°C. Powered by IEEE 802.3af Type 1 Class 3 midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan not included.	1,029
AXIS P1367-E BAREBONE	1	1		0763-031	0763-031	0763-031	AXIS P1367-E Barebone. No lens. Midspan not included.	926
AXIS P1377	1	20	To be launched	01808-001	01808-001	01808-001	5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-10 mm F1.2 P-iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. PoE class 3 or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	771
AXIS P1377 BAREBONE	1	20	To be launched	01808-031	01808-031	01808-031	AXIS P1377 Barebone in single pack. No lens. No power supply.	720
AXIS P1377-LE	1	20	To be launched	01809-001	01809-001	01809-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, 5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. OptimizeddIR, a power-efficient 850nm IR LED technology covering 50 meters (130 feet). Includes an IR corrected varifocal 2.8-10 mm F1.2 P-iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included.	1,029
AXIS P1377-LE BAREBONE	1	20	To be launched	01809-031	01809-031	01809-031	AXIS P1377-LE Barebone. No lens. Midspan not included.	977

AXIS P1368-E	1	20		01109-001	01109-001	01109-001	Outdoor, 4K Ultra HD (8MP) camera, day/night, fixed box camera providing Forensic WDR and Lightfinder for demanding light conditions. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with P-Iris, remote zoom and focus for installation (camera also supports P-Iris and DC-iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. I/O for alarm/event handling, Memory card slot for optional local video storage. Serial port for RS422/485 communication NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +55°. Powered by IEEE 802.3af Type 1 Class 3 midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan not included.	1,132
AXIS P1368-E BAREBONE	1	1		01109-031	01109-031	01109-031	AXIS P1368-E Barebone. No lens. Midspan not included.	1,029
AXIS P1378	1	20	To be launched	01810-001	01810-001	01810-001	4K resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Features a 1/1.8" image sensor. Includes an IR corrected varifocal 3.9-10 mm F1.5 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4K at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. PoE class 3 or 12-28VDC input, includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	874
AXIS P1378 BAREBONE	1	20	To be launched	01810-031	01810-031	01810-031	AXIS P1378 Barebone in single pack. No lens. No power supply.	823
AXIS P1378-LE	1	20	To be launched	01811-001	01811-001	01811-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, 4K resolution, day/night, fixed box camera providing providing Forensic WDR and Lightfinder technology. Features a 1/1.8" image sensor. Optimized IR, a power-efficient 850nm IR LED technology covering 40 meters (130 feet). Includes an IR corrected varifocal 3.9-10 mm F1.5 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4K at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR Illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included.	1,132
AXIS P1378-LE BAREBONE	1	20	To be launched	01811-031	01811-031	01811-031	AXIS P1378-LE Barebone. No lens. Midspan not included	1,080

AXIS P1435-LE	1	700		0777-001	0777-001	0777-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 3-10.5 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Video motion detection, active tampering alarm, corridor format, Lightfinder, Zipstream technology and WDR – Forensic Capture. I/O ports, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 30 meters (100 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 60 °C (-22 °F to 140 °F).	617
AXIS P1435-LE 22MM	1	100		0890-001	0890-001	0890-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 10-22 mm P-iris lens . Remote 2 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Video motion detection, active tampering alarm, corridor format, Lightfinder, Zipstream technology and WDR – Forensic Capture. I/O ports, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 50 meters (164 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 60 °C (-22 °F to 140 °F).	668
AXIS P1445-LE	1	200		01506-001	01506-001	01506-001	Compact outdoor, HDTV, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens with remote 3x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps.. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 40 meters (131 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	720
AXIS P1447-LE	1	400		01054-001	01054-001	01054-001	Compact outdoor, 5MP resolution, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens with remote 3x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	771

AXIS P1448-LE	1	300		01055-001	01055-001	01055-001	Compact outdoor, 4K Ultra HD (8MP) resolution, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-9.8 mm F1.6 P-iris lens with remote 3.5x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. Optimized IR, a power-efficient IR LED technology covering 25 meters (82 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C/-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	977
AXIS Q1615 Mk II	1	20		0883-001	0883-001	0883-001	HDTV, Day/night fixed camera providing WDR – Forensic Capture and Lightfinder for demanding light conditions. Varifocal 2.8-8.5 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-Iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps second and 720p/1MP resolution at 120 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Scene profiles.Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Power supply not included.	1,029
AXIS Q1615 Mk II BAREBONE	1	1		0883-041	0883-041	0883-041	AXIS Q1615 Mk II Barebone in single pack. No lens. No power supply.	926
AXIS Q1615-E Mk II	1	100		0884-001	0884-001	0884-001	Outdoor, NEMA 4X, IP66 and IK10-rated, HDTV, Day/night fixed camera providing WDR – Forensic Capture and Lightfinder for demanding light conditions. Varifocal 2.8-8.5 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-Iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps second and 720p/1MP resolution at 120 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Scene profiles.Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Arctic Temperature Control, operation in -30°C to 60°C (-22 °F to 140 °F) when powered by IEEE 802.3af midspan or -40°C to 60°C (-40 °F to 140 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	1,338
AXIS Q1645	1	20		01222-001	01222-001	01222-001	1/2" image sensor, HDTV, Day/night fixed camera providing Forensic WDR and Lightfinder for demanding light conditions. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-Iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles.Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	1,235
AXIS Q1645 BARE BONE	1	2		01222-041	01222-041	01222-041	AXIS Q1645 Barebone in single pack. No lens. No power supply.	1,029

AXIS Q1645-LE	1	30		01223-001	01223-001	01223-001	1/2" image sensor, outdoor, NEMA 4X, IP66 and IK10-rated HDTV, day/night fixed camera providing OptimizedIR, Forensic WDR and Lightfinder. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus. Support for CS-mount P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Zipstream for reduced bandwidth and storage. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio and I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start up in -40°C to 60°C (-40 °F to 140 °F). Includes a removable sunshield and wall bracket. Midspan not included.	1,544
AXIS Q1647	1	20		01051-001	01051-001	01051-001	1/2" sensor, 5 MP, Day/night fixed camera providing Forensic WDR and Lightfinder for demanding light conditions. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; 5 MP at 30 fps with Forensic WDR, and 4 MP at up to 60 fps without Forensic WDR. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	1,441
AXIS Q1647 BARE BONE	1	3		01051-041	01051-041	01051-041	AXIS Q1647 Barebone in single pack. No lens. No power supply.	1,235
AXIS Q1647-LE	1	30		01052-001	01052-001	01052-001	1/2" sensor, outdoor, NEMA 4X, IP66 and IK10-rated, 5 MP, Day/night fixed camera providing OptimizedIR, Forensic WDR and Lightfinder. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus. Support for CS-mount P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; 5 MP at 30 fps with Forensic WDR, and 4 MP at up to 60 fps without Forensic WDR. Zipstream for reduced bandwidth and storage. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm and shock detection. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio and I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start up in -40°C to 60°C (-40 °F to 140 °F). Includes a removable sunshield and wall bracket. Midspan not included.	1,750

AXIS Q1659 BAREBONE	1	1		01568-031	01568-031	01568-031	<p>Note: Before the order is processed, this product requires an End User Information statement to be submitted to order@axis.com</p> <p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	5,046
AXIS Q1659 10-22MM F/3.5-4.5	1	2		0967-001	0967-001	0967-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	6,076
AXIS Q1659 24MM F/2.8	1	1		0962-001	0962-001	0962-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	5,149

AXIS Q1659 35MM F/2	1	1		0963-001	0963-001	0963-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	6,076
AXIS Q1659 50MM F/1.4	1	1		0964-001	0964-001	0964-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	5,561
AXIS Q1659 85MM F/1.2	1	1		0965-001	0965-001	0965-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	8,393

AXIS Q1659 100MM F/2.8	1	1		0966-001	0966-001	0966-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	6,694
AXIS Q1659 70-200MM F/2.8	1	1		0968-001	0968-001	0968-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	8,651
AXIS Q1700-LE	1	40		01782-001	01782-001	01782-001	<p>Robust outdoor, color 2 MP/1080p HDTV license plate camera for sharp license plate images day and night. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p / 2MP resolution at up to 50/60 fps.</p> <p>Varifocal 18–137 mm, 8x optical zoom lens, 16°-2.3° HFOV, F2.9 with remote zoom and installation focus. License plate capture range 20-50 meter at night with built-in OptimizedIR at speeds up to 130 km/h (81 mph)</p> <p>Includes license plate capture assistant for easy setup, pixel counter, shock detection, active tampering alarm, defogging and electronic image stabilization.</p> <p>Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage.</p> <p>Integrated bracket for easy mounting on wall and ceiling. Dark grey (NCS S5502-B) casing, black fixed metal weather shield with anti-glare coating.</p> <p>NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C (-40 °F to 140 °F).</p> <p>Powered by PoE (IEEE 802-3af), RJ45 or IDC punchdown connector, 20-28 V DC or 20-24 V AC. License plate recognition software, power supply or midspan not included.</p>	1,338

AXIS Q1765-LE PTMOUNT	1	20	Discontinued - contact Order dept for availability	0644-001	0644-001	0644-001	Outdoor, IP66 and NEMA 4X-rated, 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Integrated IR LED illumination. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR- dynamic contrast. Video motion detection and active tampering alarm. Serial port supporting RS422/485 communication for connection to a pan-tilt motor. MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -40°C to +50°C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes a removable sunshield. Power supply, midspan or pan-tilt motor not included.	1,441
AXIS Q1775	1	1	Discontinued - contact Order dept for availability	0751-001	0751-001	0751-001	1080p HDTV camera with 10x zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max. HDTV 1080p resolution at 50/60 fps. WDR-Dynamic Capture (130dB@ 30 fps and 90dB@ 60 fps). Video motion detection, Gatekeeper functionality and active tampering alarm. Two way audio in 48KHz, I/O and serial port for RS485/RS422 communication. SDHC/SDXC memory card slot for optional local video storage. Operation in 0 °C to +50 °C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes stand for wall or ceiling mount. Power supply not included.	1,338
AXIS Q1775-E	1	1	Discontinued - contact Order dept for availability	0752-001	0752-001	0752-001	Outdoor, IP66- and NEMA 4X-rated, 1080p HDTV camera with 10x zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max. HDTV 1080p resolution at 50/60 fps. WDR-Dynamic Capture (130dB@ 30 fps and 90dB@ 60 fps). Video motion detection, Gatekeeper functionality and active tampering alarm. Two way audio in 48KHz, I/O and serial port for RS485/RS422 communication. SD/SDHC/SDXC memory card slot for optional local video storage. Arctic Temperature Control, operation in -30°C to 50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40 °C to 50 °C (-40 °F to 122 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	1,647
AXIS Q1785-LE	1	125		01161-001	01161-001	01161-001	Robust outdoor, 2 MP/HDTV, day/night fixed bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p/2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3-137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. Includes a removable sunshield. Power supply or midspan not included.	1,235

AXIS Q1786-LE	1	50		01162-001	01162-001	01162-001	<p>Robust outdoor, 4 MP/Quad HD1440p, day/night fixed bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1440p /4MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs.</p> <p>Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus.</p> <p>Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles</p> <p>Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage.</p> <p>OptimizedIR, a power-efficient IR LED technology.</p> <p>Integrated bracket for easy mounting on wall and ceiling.</p> <p>NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. Includes a removable sunshield.</p> <p>Power supply or midspan not included.</p>	1,441
AXIS Q1798-LE	1	50		01702-001	01702-001	01702-001	<p>Robust outdoor, NEMA 4X, IP66/67 and IK10-rated 10 MP/ 4K, day/night, fixed bullet camera providing Forensic WDR and Lightfinder 2.0 technology. Features a 4/3" type image sensor, built-in varifocal 12–48 mm, 4 x optical Canon zoom lens, 90°-21° HFOV, F1.7 with remote zoom and autofocus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4K at 30 fps /10MP resolution at 20 fps.</p> <p>Axis Zipstream technology for reduced bandwidth and storage needs.</p> <p>Includes analytics AXIS Guard Suite, Video motion detection, shock detection and active tampering alarm. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Audio mic/line in, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage.</p> <p>OptimizedIR, a power-efficient IR LED technology.</p> <p>Integrated bracket for easy mounting on wall and ceiling.</p> <p>Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable sunshield, Torx T20 allen key, IP66/67- rated cable glands and optional IDC punch connector.</p> <p>Power supply or midspan not included.</p>	1,853
AXIS Q1941-E 7MM 8.3 FPS	1	4	6 weeks delivery	0782-001	0782-001	0782-001	<p>Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	2,883
AXIS Q1941-E 13MM 8.3 FPS	1	3	6 weeks delivery	0783-001	0783-001	0783-001	<p>Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	2,883

AXIS Q1941-E 19MM 8.3 FPS	1	1	6 weeks delivery	0876-001	0876-001	0876-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2,883
AXIS Q1941-E 35MM 8.3 FPS	1	5	6 weeks delivery	0784-001	0784-001	0784-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	3,913
AXIS Q1941-E 60MM 8.3 FPS	1	3	6 weeks delivery	0785-001	0785-001	0785-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5,458
AXIS Q1941-E PT MOUNT 7MM 8.3 FPS	1	1	6 weeks delivery	0969-001	0969-001	0969-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2,883
AXIS Q1941-E PT MOUNT 13MM 8.3 FPS	1	1	6 weeks delivery	0970-001	0970-001	0970-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2,883
AXIS Q1941-E PT MOUNT 19MM 8.3 FPS	1	1	6 weeks delivery	0978-001	0978-001	0978-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2,883

AXIS Q1941-E PT MOUNT 35MM 8.3 FPS	1	1	6 weeks delivery	0971-001	0971-001	0971-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	3,913
AXIS Q1941-E PT MOUNT 60MM 8.3 FPS	1	1	6 weeks delivery	0972-001	0972-001	0972-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5,458
AXIS Q1942-E 10MM 8.3 FPS	1	4	6 weeks delivery	0915-001	0915-001	0915-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5,149
AXIS Q1942-E 19MM 8.3 FPS	1	2	6 weeks delivery	0917-001	0917-001	0917-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 19 mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5,149
AXIS Q1942-E 35MM 8.3 FPS	1	1	6 weeks delivery	0919-001	0919-001	0919-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 35 mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	6,179
AXIS Q1942-E 60MM 8.3 FPS	1	1	6 weeks delivery	0921-001	0921-001	0921-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	7,724

AXIS Q1942-E PT MOUNT 10MM 8.3 FPS	1	1	6 weeks delivery	0980-001	0980-001	0980-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5,149
AXIS Q1942-E PT MOUNT 19MM 8.3 FPS	1	1	6 weeks delivery	0982-001	0982-001	0982-001	Q1942-E PT mount 19mm Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 19mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5,149
AXIS Q1942-E PT MOUNT 35MM 8.3 FPS	1	1	6 weeks delivery	0984-001	0984-001	0984-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 35mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	6,179
AXIS Q1942-E PT MOUNT 60MM 8.3 FPS	1	1	6 weeks delivery	0986-001	0986-001	0986-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	7,724
AXIS Q2901-E 9MM 8.3 FPS	1	4		0645-001	0645-001	0645-001	AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	5,355
AXIS Q2901-E PTMOUNT 9MM 8.3 FPS	1	1		0646-001	0646-001	0646-001	AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	5,355

AXIS Q2901-E 19MM 8.3 FPS	1	1		0647-001	0647-001	0647-001	AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	5,355
AXIS Q2901-E PTMOUNT 19MM 8.3 FPS	1	1		0648-001	0648-001	0648-001	AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	5,355
AXIS F34 MAIN UNIT	1	40		0778-001	0778-001	0778-001	AXIS F34 Main Unit. 4-channel main unit to be used with any of AXIS F Sensor Units. Supports 1080p in 15/12.5 fps or 720p in full frame rate. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Supports edge storage through NAS or SD cards (optional). Two SD card slots. Power over Ethernet or 8-28 V DC input. Power supply not included.	411
AXIS F41 MAIN UNIT	1	175		0658-001	0658-001	0658-001	AXIS F41 Main Unit. To be used with any of AXIS F Series Sensor Units. Supports full HDTV 1080p and WDR - Forensic Capture. Two way audio, 4 configurable I/Os with 12 V output and RS232. Supports Edge Storage through NAS or SD card (optional). PoE and 8-28 V DC support.	462
AXIS F44 DUAL AUDIO INPUT	1	200		0936-001	0936-001	0936-001	AXIS F44 Dual Audio Input Main Unit. 4-channel main unit to be used with any of AXIS F Series Sensor Units. Supports 1080p in 15/12.5 fps or 720p in full frame rate. Two way audio, 4 configurable I/Os with 12 V output and RS232. Supports Edge Storage through NAS or SD cards (optional). Two SD card slots. PoE and 8-28 V DC support. Comes with a stereo-to-mono adapter cable that allows two audio inputs. This article replaces AXIS F44 Main Unit (0659-00x) and the US version of AXIS F44 Dual Audio Input (0936-004).	565
AXIS F1004 SENSOR UNIT	1	100		0765-001	0765-001	0765-001	AXIS F1004 Sensor Unit with a fixed lens. Provides HDTV 720p and 102° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit. A flush ceiling/wall mount kit is included.	102
AXIS F1004 BULLET SENSOR UNIT	1	10		0935-001	0935-001	0935-001	AXIS F1004 Bullet Sensor Unit with a fixed lens. Bullet-style mechanics enabling easy mounting on walls or ceilings and with the ability to tilt and rotate. Provides HDTV 720p and 102° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit.	123
AXIS F1004 PINHOLE SENSOR UNIT	1	150		01003-001	01003-001	01003-001	AXIS F1004 Pinhole Sensor Unit. Pinhole lens for extremely discreet surveillance. Provides HDTV 720p and 57° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit. Comes with a mounting bracket for the sensor unit.	123
AXIS F34 SURVEILLANCE SYSTEM	1	15		0779-003	0779-006	0779-002	AXIS F34 Surveillance System. Includes one AXIS F34 Main Unit, 4 x AXIS F1004 Sensor Units, 4 x AXIS F8214 Dome Accessory, 4 x AXIS F8224 Recessed Mount, 4 x AXIS F7315 Cable White 15 m (49 ft) for connecting sensor units to the main unit and 2 x AXIS Surveillance microSDXC card 64 GB. Comes with a power supply.	823

AXIS F1005-E SENSOR UNIT 3M	1	90		0675-001	0675-001	0675-001	AXIS F1005-E Sensor Unit with a 3 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	256
AXIS F1005-E SENSOR UNIT 12M	1	50		0676-001	0676-001	0676-001	AXIS F1005-E Sensor Unit with a 12 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	277
AXIS F1015 SENSOR UNIT 3M	1	40		0677-001	0677-001	0677-001	AXIS F1015 Sensor Unit with a 3 meter cable to the main unit. To be used with AXIS F Series Main Units. Vari-focal lens that provides 53° - 108° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	287
AXIS F1015 SENSOR UNIT 12M	1	100		0678-001	0678-001	0678-001	AXIS F1015 Sensor Unit with a 12 meter cable to the main unit. To be used with AXIS F Series Main Units. Vari-focal lens that provides 53° - 108° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	308
AXIS F1025 SENSOR UNIT 3M	1	20		0735-001	0735-001	0735-001	AXIS F1025 Sensor Unit with a 3 meter cable to the main unit. To be used with AXIS F Series Main Units. Pinhole lens that provides 92° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8202 Straight Mounting Bracket.	256
AXIS F1025 SENSOR UNIT 12M	1	30		0734-001	0734-001	0734-001	AXIS F1025 Sensor Unit with a 12 meter cable to the main unit. To be used with AXIS F Series Main Units. Pinhole lens that provides 92° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8202 Straight Mounting Bracket.	277
AXIS F1035-E SENSOR UNIT 3M	1	30		0737-001	0737-001	0737-001	AXIS F1035-E Sensor Unit with a 3 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fisheye lens that provides 194° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	256
AXIS F1035-E SENSOR UNIT 12M	1	60		0736-001	0736-001	0736-001	AXIS F1035-E Sensor Unit with a 12 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fisheye lens that provides 194° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	277
AXIS F4005-E DOME SENSOR UNIT	1	50		0775-001	0775-001	0775-001	AXIS F4005-E Dome Sensor Unit with a 12-meter (39-feet) cable to an AXIS F Series Main Unit. Comes with a clear dome cover and damask at the back that makes it IK09 and IP66 rated. Fixed lens that provides 110° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit.	298
AXIS F4005 DOME SENSOR UNIT	1	5		0798-001	0798-001	0798-001	AXIS F4005 Dome Sensor Unit with a 12-meter (39-feet) cable to an AXIS F Series Main Unit. Recessed dome without a clear dome cover. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit.	287
AXIS FA1080-E 4MM 8.3 FPS	1	20		01728-001	01728-001	01728-001	<p>AXIS FA1080-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable.</p> <p>This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	668

AXIS FA1105 SENSOR UNIT	1	125		0913-001	0913-001	0913-001	AXIS FA1105 is a discreet indoor sensor unit with 111° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a small hole visible for the lens. AXIS FA1105 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	143
AXIS FA1125 SENSOR UNIT	1	125		0914-001	0914-001	0914-001	AXIS FA1125 is an extremely discreet indoor, pin hole lens, Sensor Unit with a 91° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a pinhole visible for the lens. AXIS FA1125 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	153
AXIS FA3105-L EYEBALL SENSOR UNIT	1	20		01026-001	01026-001	01026-001	AXIS FA3105-L is a compact eyeball sensor unit with built in IR illumination (15 m / 49 ft range of reach) for use with AXIS FA Main Unit. It has 103° horizontal field of view and 1080p HDTV resolution with Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to the main unit.	153
AXIS FA4090-E 4MM 8.3 FPS	1	20		01729-001	01729-001	01729-001	AXIS FA4090-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The dome housing makes it easy to install and direct the sensor unit to cover your area of interests. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable. This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	720
AXIS FA4115 SENSOR UNIT	1	15		01001-001	01001-001	01001-001	AXIS FA4115 is a compact varifocal dome sensor unit with 53° to 99° horizontal field of view for use with an AXIS FA Main Unit. AXIS FA4115 provides a 1080p resolution a Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8-m (26 ft.) cable for connection to a main unit.	184
AXIS FA54 MAIN UNIT	1	30		0878-003	0878-006	0878-002	AXIS FA54 is a modular camera Main Unit and can stream full frame rate HDTV 1080p videos from four sensor units simultaneously using one IP address. It has an HDMI port for connection to a surveillance or public view monitor, Forensic WDR (wide dynamic range) that is optimized for low light and motion, Axis Zipstream, two microphone inputs and one audio out, I/O port and two micro SD card slots for local storage.	462
AXIS Q1659 55-250MM F/4-5.6	1	1		01118-001	01118-001	01118-001	Professional photography meets video surveillance AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances. It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes. AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements. > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing	5,355

AXIS M3015	1	200		01151-001	01151-001	01151-001	Ultra-discreet, indoor fixed mini dome for recessed mounting in ceiling or wall. Fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	277
AXIS M3016	1	2		01152-001	01152-001	01152-001	Ultra-discreet, indoor fixed mini dome for recessed mounting in ceiling or wall. Fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 3 MP at 30 fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	380
AXIS M3044-V	1	400		0802-001	0802-001	0802-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	205
AXIS M3044-WV	1	8		0803-003	0803-006	0803-002	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Power supply included.	236
AXIS M3045-V	1	850		0804-001	0804-001	0804-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	277
AXIS M3045-WV	1	20		0805-003	0805-006	0805-002	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Power supply included.	308
AXIS M3046-V 1.8MM	1	80		01116-001	01116-001	01116-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed 1.8mm lens. Multiple, individually configurable H.264 and Motion JPEG streams; max 3 MP at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	380
AXIS M3046-V 2.4mm	1	100		0806-001	0806-001	0806-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max 4 MP at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	380

AXIS M3047-P	1	250		0808-001	0808-001	0808-001	Ultra-compact, indoor fixed mini dome with 6 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 30 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet. Midspan not included.	483
AXIS M3048-P	1	50		01004-001	01004-001	01004-001	Ultra-compact, indoor fixed mini dome with 12 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview in up to 30 fps and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 15 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet. Midspan not included.	689
AXIS M3024-LVE	1	20		0535-001	0535-001	0535-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed lens and built-in IR illumination. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included	565
AXIS M3025-VE	1	10		0536-001	0536-001	0536-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	565
AXIS M3026-VE	1	60		0547-001	0547-001	0547-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed, 106° lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps or 3 MP resolution at 20 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	668
AXIS M3027-PVE	1	30	Discontinued - contact Order dept for availability	0556-001	0556-001	0556-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation, offering 360°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.	771
AXIS M3037-PVE	1	20		0548-001	0548-001	0548-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation, offering 360°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Two-way, echo-free audio communication with built-in microphone and speaker. SIP support for IP phone system integration. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.	823

AXIS M3057-PLVE	1	200		01177-001	01177-001	01177-001	360°/180° fixed dome with 6 MP sensor and support for Forensic WDR, Lightfinder and OptimizedIR illumination. Vandal-resistant casing in flat design, for outdoor or indoor installation. Provides complete 360° overview in up to 30 fps with WDR and 60 fps with WDR disabled. Dewarped panorama, quad, corner, corridor and up to four digital PTZ views. Client-side dewarping also supported. Multiple, individually configurable H.264 and Motion JPEG streams, Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes. Midspan not included.	668
AXIS M3058-PLVE	1	80		01178-001	01178-001	01178-001	360°/180° fixed dome with 12 MP sensor and support for Forensic WDR, Lightfinder and OptimizedIR illumination. Vandal-resistant casing in flat design, for outdoor or indoor installation. Provides complete 360° overview in up to 20 fps with WDR and 30 fps with WDR disabled. Dewarped panorama, quad, corner, corridor and up to four digital PTZ views. Client-side dewarping also supported. Multiple, individually configurable H.264 and Motion JPEG streams, Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes. Midspan not included.	874
AXIS M3104-L	1	30		0865-001	0865-001	0865-001	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	256
AXIS M3104-LVE	1	30		0866-001	0866-001	0866-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	308
AXIS M3105-L	1	350		0867-001	0867-001	0867-001	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	329
AXIS M3105-LVE	1	200		0868-001	0868-001	0868-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	380
AXIS M3106-L MK II	1	125		01036-001	01036-001	01036-001	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4MP resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	432

AXIS M3106-LVE MK II	1	100		01037-001	01037-001	01037-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	483
AXIS M3205-LVE	1	20	New	01517-001	01517-001	01517-001	Fixed dome with built-in IR illumination and IK10 vandal-resistant casing, designed for easy outdoor or indoor installation. Fixed lens, 100° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 1080p at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection, tampering alarm and supervised digital input / digital output for alarm/event handling. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	514
AXIS M3206-LVE	1	20	New	01518-001	01518-001	01518-001	Fixed dome with built-in IR illumination and IK10 vandal-resistant casing, designed for easy outdoor or indoor installation. Fixed lens, wide 105°/79° horizontal/vertical field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection, tampering alarm and supervised digital input / digital output for alarm/event handling. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	617
AXIS M4206-V	1	250		01240-001	01240-001	01240-001	Ultra-compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting on wall or ceiling. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 3MP for wide 4:3 view, 1080p for 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Midspan not included.	432
AXIS M4206-LV	1	250		01241-001	01241-001	01241-001	Ultra-compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting on wall or ceiling. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 3MP for wide 4:3 view, 1080p for 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Midspan not included.	483
AXIS P3224-V MKII	1	200		0950-001	0950-001	0950-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 2.8-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	432

AXIS P3224-LV MKII	1	100		0990-001	0990-001	0990-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 2.8-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	514
AXIS P3225-V MKII	1	850		0952-001	0952-001	0952-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	514
AXIS P3225-VE MKII	1	300		0953-001	0953-001	0953-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder. IK10 vandal-resistant outdoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	638
AXIS P3225-LV MKII	1	1200		0954-001	0954-001	0954-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	596
AXIS P3225-LVE MKII	1	1100		0955-001	0955-001	0955-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and weather shield against sun, rain or snow.	720
AXIS P3227-LV	1	500		0885-001	0885-001	0885-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust- and IK08 vandal-resistant indoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	802

AXIS P3227-LVE	1	300		0886-001	0886-001	0886-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	926
AXIS P3228-LV	1	300		0887-001	0887-001	0887-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust- and IK08 vandal-resistant indoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 4K (8MP) at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	1,008
AXIS P3228-LVE	1	175		0888-001	0888-001	0888-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 4K (8MP) at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,132
AXIS P3235-LV	1	40		01443-001	01443-001	01443-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	648
AXIS P3235-LVE	1	30		01199-001	01199-001	01199-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	771

AXIS P3245-V	1	1400		01591-001	01591-001	01591-001	Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	514
AXIS P3245-LV	1	2000		01592-001	01592-001	01592-001	Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	596
AXIS P3245-VE	1	900		01594-001	01594-001	01594-001	Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	638
AXIS P3245-LVE	1	2000		01593-001	01593-001	01593-001	Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	720
AXIS P3367-V	1	300		0406-001	0406-001	0406-001	5MP, day/night, fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	1,029

AXIS P3367-VE	1	50		0407-001	0407-001	0407-001	5MP, day/night, fixed dome with vandal-resistant, IP66-rated outdoor casing. Varifocal 3-9 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	1,235
AXIS P3374-V	1	500		01056-001	01056-001	01056-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	617
AXIS P3374-LV	1	100		01058-001	01058-001	01058-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	720
AXIS P3375-V	1	400		01060-001	01060-001	01060-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	720
AXIS P3375-LV	1	125		01062-001	01062-001	01062-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	823
AXIS P3375-VE	1	300		01061-001	01061-001	01061-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. IK10 vandal-resistant outdoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Operation in -40°C to 55°C (-40 °F to 131 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	926

AXIS P3375-LVE	1	50		01063-001	01063-001	01063-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Operation in -40 °C to 55 °C (-40 °F to 131 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,029
AXIS P3707-PE	1	1	Discontinued - contact Order dept for availability	0815-001	0815-001	0815-001	Flexible multisensor fixed camera with four 1080p sensors. The lenses can be adjusted to provide a 108° to 54° horizontal field of view for either a wide, panoramic view, or detailed, zoomed-in views. The lenses can be rotated to support vertically oriented scenes in Axis' Corridor Format. Supports individually configurable video streams from each camera head, as well as quad view streaming, enabling 4x 1080p resolution videos at 12.5/15 fps or 4x 720p resolution videos at full frame rate. Axis' Zipstream technology is supported to lower bandwidth and storage requirements. PoE Class 2.	1,235
AXIS P3717-PLE	1	300		01504-001	01504-001	01504-001	AXIS P3717-PLE Network Camera is a compact 8-megapixel camera with four varifocal lenses enabling overview and detailed surveillance. With one IP address and one network cable, the four-camera-in-one unit provides a flexible, cost-effective solution for multidirectional surveillance. 360° IR illumination, Forensic WDR and Lightfinder technology provides excellent video quality in any light conditions. Each camera head can be individually positioned (pan, tilt, roll and twist) along a circular track. Remote zoom and focus makes it easy to install and the clear cover, with no sharp edges, ensures undistorted views in all directions. The camera comes with an integrated weathershield.	1,389
AXIS P3719-PLE	1	100	New	01500-001	01500-001	01500-001	AXIS P3719-PLE Network Camera is a compact 15-megapixel camera with four varifocal lenses (4 x Quad HD) enabling overview and detailed surveillance. With one IP address and one network cable, the four-camera-in-one unit provides a flexible, cost-effective solution for multidirectional surveillance. 360° IR illumination, WDR and Lightfinder technology provides excellent video quality in any light conditions. Each camera head can be individually positioned (pan, tilt, roll, and twist) along a circular track. Remote zoom and focus makes it easy to install and the clear cover, with no sharp edges, ensures undistorted views in all directions. The camera has an integrated weathershield.	1,647
AXIS P3807-PVE	1	90		01048-001	01048-001	01048-001	AXIS P3807-PVE Network Camera is a fixed dome camera with multiple sensors, providing an easy, reliable and cost-efficient one-camera installation – reducing installation time, cabling and VMS license costs. Thanks to its excellent image sensors, along with Forensic WDR and Lightfinder technology, it provides great video quality in any light conditions. Its four sensors give a seamless 180° panoramic overview, at up to 30 fps in 8 MP resolution. The camera is easy to install as recessed, flush, pendant, back-to-back, and comes with adjustable pre-set camera positions. •Seamlessly stitched images •180° horizontal and 90° vertical coverage •8 MP resolution at full frame rate •Axis Lightfinder and Forensic WDR •Axis Zipstream for reduced bandwidth and storage needs	1,389
AXIS P3904-R Mk II	1	30		01078-001	01078-001	01078-001	720p fixed dome onboard camera with male RJ-45 network connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	462

AXIS P3904-R MK II BULK 10PCS	1	30		01078-021	01078-021	01078-021	AXIS P3904-R MkII (RJ45) in bulk 10-pack. 720p fixed dome onboard camera with male RJ-45 network connector.	4,393
AXIS P3904-R MK II BULK 50 PCS	1	10		01078-031	01078-031	01078-031	AXIS P3904-R MkII (RJ45) in bulk 50-pack. 720p fixed dome onboard camera with male RJ-45 network connector.	21,938
AXIS P3904-R MK II M12	1	40		01071-001	01071-001	01071-001	720p fixed dome onboard camera with female M12 D-coded connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	462
AXIS P3904-R MK II M12 BULK 10PCS	1	30		01071-021	01071-021	01071-021	AXIS P3904-R MkII (M12) in bulk 10-pack. 720p fixed dome onboard camera with female M12 D-coded connector.	4,393
AXIS P3904-R MK II M12 BULK 50PCS	1	1		01071-031	01071-031	01071-031	AXIS P3904-R MkII (M12) in bulk 50-pack. 720p fixed dome onboard camera with female M12 D-coded connector.	21,938
AXIS P3905-R Mk II	1	70		01072-001	01072-001	01072-001	1080p fixed dome onboard camera with male RJ-45 network connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	565
AXIS P3905-R MK II BULK 10PCS	1	7		01072-021	01072-021	01072-021	AXIS P3905-R MkII (RJ45) in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector.	5,371
AXIS P3905-R MK II BULK 50 PCS	1	2		01072-031	01072-031	01072-031	AXIS P3905-R MkII (RJ45) in bulk 50-pack. 1080p fixed dome onboard camera with male RJ-45 network connector.	26,779
AXIS P3905-R Mk II M12	1	20		01073-001	01073-001	01073-001	1080p fixed dome onboard camera with female M12 D-coded connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	565
AXIS P3905-R MK II M12 BULK 10 PCS	1	3		01073-021	01073-021	01073-021	AXIS P3905-R MkII (M12) in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector.	5,371
AXIS P3905-R MK II M12 BULK 50 PCS	1	2		01073-031	01073-031	01073-031	AXIS P3905-R MkII (M12) in bulk 50-pack. 1080p fixed dome onboard camera with female M12 D-coded connector.	26,779
AXIS P3905-R MK II BAREBONE 10P	1	1		01072-041	01072-041	01072-041	AXIS P3905-R Mk II (RJ45) with no lens in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector. Lenses sold separately. Note: Avoid installing lenses in dusty environments. To reduce the risk of dust falling into the sensor, hold the camera with the lens opening facing down.	5,176
AXIS P3915-R Mk II	1	50		01074-001	01074-001	01074-001	1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	617
AXIS P3915-R MK II BULK 10 PCS	1	5		01074-021	01074-021	01074-021	AXIS P3915-R MkII (RJ45) in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Accessory kit not included in 10-pack.	5,861
AXIS P3915-R MK II BULK 50 PCS	1	1		01074-031	01074-031	01074-031	AXIS P3915-R MkII (RJ45) in bulk 50-pack. 1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Accessory kit not included in 50-pack.	29,251
AXIS P3915-R Mk II M12	1	10		01075-001	01075-001	01075-001	1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	617
AXIS P3915-R MK II M12 BULK 10 PCS	1	1		01075-021	01075-021	01075-021	AXIS P3915-R MkII (M12) in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Accessory kit not included in 10-pack.	5,861
AXIS P3915-R MK II M12 BULK 50 PCS	1	1		01075-031	01075-031	01075-031	AXIS P3915-R MkII (M12) in bulk 50-pack. 1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Accessory kit not included in 50-pack.	29,251
AXIS P3905-R MK II M12 BAREBONE 10P	1	1		01073-041	01073-041	01073-041	AXIS P3905-R Mk II (M12) with no lens in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector. Lenses sold separately. Note: Avoid installing lenses in dusty environments. To reduce the risk of dust falling into the sensor, hold the camera with the lens opening facing down.	5,176
AXIS P3905-RE M12	1	2	Discontinued - contact Order dept for availability	0663-001	0663-001	0663-001	Fixed dome mobile surveillance camera for outdoors use on buses, trams, trucks and emergency vehicles. IP69K and IK09 rated. Fixed 6 mm lens providing 55° horizontal FOV. Flat, discreet and tamper-resistant casing. Supports H.264 and Motion JPEG streams: max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. M12 network connector, Power over Ethernet, microSD card slot for Edge storage support. Includes lens tool and top cover tool.	565

AXIS P3905-RE M12 BULK 10PCS	1	1	Discontinued - contact Order dept for availability	0663-021	0663-021	0663-021	Fixed dome mobile surveillance camera for outdoors use on buses, trams, trucks and emergency vehicles. IP69K and IK09 rated. Fixed 6 mm lens providing 55° horizontal FOV. Flat, discreet and tamper-resistant casing. Supports H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. M12 network connector, Power over Ethernet, microSD card slot for Edge storage support. Includes lens tool and top cover tool. 10 PCS.	5,458
AXIS P9106-V BRUSHED STEEL	1	10		01553-001	01553-001	01553-001	3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Elegant brushed steel design with no visible screws. Dust- and waterproof (IP66) casing, WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. Color: Brushed stainless steel.	668
AXIS P9106-V WHITE	1	30		01620-001	01620-001	01620-001	3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Ligature-resistant design with dust- and waterproof (IP66) casing, WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. White in color.	617
AXIS Q3505-V 9MM MkII	1	1	Discontinued - contact Order dept for availability	0872-001	0872-001	0872-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder in a discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p video at 30 fps with WDR, and 1080p at up to 60 fps or 720p at up to 120 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	926
AXIS Q3505-V 22MM MkII	1	1	Discontinued - contact Order dept for availability	0873-001	0873-001	0873-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder in a discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p video at 30 fps with WDR, and 1080p at up to 60 fps or 720p at up to 120 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	1,029
AXIS Q3505-VE 9MM MkII	1	1	Discontinued - contact Order dept for availability	0874-001	0874-001	0874-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder in an IK10+ vandal-resistant outdoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p video at 30 fps with WDR, and 1080p at up to 60 fps or 720p at up to 120 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,080

AXIS Q3505-SVE 9MM MKII	1	1	Discontinued - contact Order dept for availability	0773-001	0773-001	0773-001	Day/night fixed dome in a stainless steel (marine-grade SS 316L) outdoor casing with nylon dome cover, offering high corrosion resistance and IK10+ (50 joules) vandal resistance. Support for WDR – Forensic Capture and Lightfinder. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p video at 30 fps with WDR, and 1080p at up to 60 fps or 720p at up to 120 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in extended temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	1,389
AXIS Q3505-VE 22MM MKII	1	1	Discontinued - contact Order dept for availability	0875-001	0875-001	0875-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder in an IK10+ vandal-resistant outdoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p video at 30 fps with WDR, and 1080p at up to 60 fps or 720p at up to 120 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,183
AXIS Q3505-SVE 22MM MKII	1	1	Discontinued - contact Order dept for availability	0774-001	0774-001	0774-001	Day/night fixed dome in a stainless steel (marine-grade SS 316L) outdoor casing with nylon dome cover, offering high corrosion resistance and IK10+ (50 joules) vandal resistance. Support for WDR – Forensic Capture and Lightfinder. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p video at 30 fps with WDR, and 1080p at up to 60 fps or 720p at up to 120 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in extended temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	1,492
AXIS Q3515-LV 9MM	1	150		01039-001	01039-001	01039-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.	874

AXIS Q3515-LV 22MM	1	125		01044-001	01044-001	01044-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.	926
AXIS Q3515-LVE 9MM	1	400		01041-001	01041-001	01041-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder, and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,029
AXIS Q3515-LVE 22MM	1	125		01046-001	01046-001	01046-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder, and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,080
AXIS Q3517-LV	1	30		01021-001	01021-001	01021-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.	1,132

AXIS Q3517-LVE	1	80		01022-001	01022-001	01022-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,286
AXIS Q3517-SLVE	1	15		01237-001	01237-001	01237-001	Day/night fixed dome in a stainless steel (marine-grade SS 316L) outdoor casing, offering high corrosion resistance and IK10+ (50 joules) vandal resistance. Support for Forensic WDR, Lightfinder and OptimizedIR IR illumination. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall/ceiling or junction boxes.	1,389
AXIS Q3527-LVE	1	10		01565-001	01565-001	01565-001	Fixed dome with enhanced security features: signed firmware and secure boot ensure firmware authenticity, and a Trusted Platform Module (TPM) secures certificates and cryptographic keys. Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for local storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,389
AXIS Q3518-LVE	1	20		01493-001	01493-001	01493-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. Up to 4K/8MP at 30 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1,389

AXIS Q3615-VE	1	15		0743-001	0743-001	0743-001	Day/night fixed dome with 1/2" sensor, providing WDR – Forensic Capture and Lightfinder for demanding light conditions. IK10 vandal-resistant outdoor casing. Pan/tilt/roll/zoom for remote installation and readjustment. Motorized varifocal 4.1-9 mm P-Iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; HDTV 1080p at up to 60 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Memory card slot for optional local video storage. Operation in wide temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and substantial weather shield against sun, rain or snow.	1,389
AXIS Q3617-VE	1	8		0744-001	0744-001	0744-001	Day/night fixed dome with 1/2" sensor, providing WDR – Forensic Capture and Lightfinder for demanding light conditions. IK10 vandal-resistant outdoor casing. Pan/tilt/roll/zoom for remote installation and readjustment. Motorized varifocal 4.1-9 mm P-Iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; up to 4MP @ 30 fps with WDR, 6 MP @ 20 fps without WDR. Zipstream for reduced bandwidth and storage needs. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Memory card slot for optional local video storage. Operation in wide temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and substantial weather shield against sun, rain or snow.	1,595
AXIS Q3708-PVE	1	100		0801-001	0801-001	0801-001	180° multi-sensor, day/night fixed dome in an IK10 vandal-resistant outdoor casing. Fixed focal, multi-megapixel lenses, focused from factory. 3 x QHD resolution, up to 15MP total in 4:3 format. WDR Forensic Capture, Zipstream and one single IP address. Operation in wide temperature range powered by standard Power over Ethernet Plus. Midspan not included. Designed for pendant or wall mount arm with same bayonet joint interface as Axis' PTZ domes. Includes weather shield against sun, rain or snow, easily repaintable to blend in with the environment.	2,059
AXIS Q3709-PVE	1	125		0664-001	0664-001	0664-001	Multi-sensor, day/night fixed dome in an IK10 vandal-resistant outdoor casing. Fixed focal, multi-megapixel lenses, focused from factory. Multiple, individually configurable H.264 and Motion JPEG streams; high-quality 4K video in 30 fps from each of 3 sensors and up to 33 MP resolution in total, together providing a 180° view. Video motion detection and active tampering alarm. Operation in wide temperature range powered by standard Power over Ethernet Plus. Midspan not included. Designed for pendant or wall mount arm with same bayonet joint interface as Axis' PTZ domes. Includes weather shield against sun, rain or snow, easily repaintable to blend in with the environment.	2,471
AXIS Q8414-LVS METAL	1	50		0709-001	0709-001	0709-001	AXIS Q8414-LVS Network Camera Metal is a brushed stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	1,338

AXIS Q8414-LVS WHITE	1	8		0710-001	0710-001	0710-001	AXIS Q8414-LVS Network Camera White is a powder coated stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5-6 mm, 105°-49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	1,338
PTZ								
AXIS Q8641-E 35MM 8.3 FPS 24V	1	1		01120-001	01120-001	01120-001	High accuracy outdoor PT positioning thermal camera. 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5,973
AXIS Q8642-E 60MM 8.3 FPS 24V	1	1		01122-001	01122-001	01122-001	High accuracy outdoor PT positioning thermal camera. 640x480 resolution, 8.3 fps and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	9,784
AXIS Q8685-E 24V AC/DC	1	20		0862-001	0862-001	0862-001	High accuracy outdoor PTZ positioning camera. HDTV 1080p video, 30x optical zoom, focus recall, extreme light sensitivity and Axis Zipstream. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated long-life silicone wiper for remote maintenance, and integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included)	3,707
AXIS Q8685-LE 24V AC/DC	1	5		0864-001	0864-001	0864-001	High accuracy outdoor PTZ positioning camera with IR illuminators. HDTV 1080p video, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance, and integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included)	5,355

AXIS Q8741-E 35MM 8.3 FPS 24V	1	1		0823-001	0823-001	0823-001	High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	10,299
AXIS Q8741-LE 35MM 8.3 FPS 24V	1	1		01012-001	01012-001	01012-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	11,947
AXIS Q8742-E ZOOM 8.3 FPS 24V	1	1		0829-001	0829-001	0829-001	High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	22,659

AXIS Q8742-E 35MM 8.3 FPS 24V	1	1		0827-001	0827-001	0827-001	High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	13,389
AXIS Q8742-LE 35MM 8.3 FPS 24V	1	1		01016-001	01016-001	01016-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera only need one IP address and supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	15,037
AXIS Q8742-LE ZOOM 8.3 FPS 24V	1	1		01018-001	01018-001	01018-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	24,307
Ptz Dome								
AXIS Q6125-LE 50HZ	1	200		01233-003	01233-006	01233-002	Top of the line PTZ with IR, HDTV 1080 and 30x optical zoom, H264/265 with Zipstream and Motion JPEG. IP66 for both indoor and outdoor use, WDR . Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper analytics. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan with fiber slot and RJ45 input included.	3,089
AXIS M5054	1	90		01079-001	01079-001	01079-001	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 720p (1280x720) 25/30fps in H.264 with Zipstream and Motion JPEG. IP51 protection against dust and water. Basic analytics are included. Only PoE, midspan not included. Surface ceiling mounting brackets included	514

AXIS Q6125-LE 60HZ	1	20					Top of the line PTZ with IR, HDTV 1080 and 30x optical zoom, H264/265 with Zipstream and Motion JPEG. IP66 for both indoor and outdoor use, WDR . Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper analytics. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan with fiber slot and RJ45 input included.	3,089
AXIS M5055	1	15		01081-001	01081-001	01081-001	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 1080p (1920x1080) 30/25fps in H.264 with Zipstream and Motion JPEG. IP51 protection against dust and water. Basic analytics are included. Only PoE, midspan not included. Surface ceiling mounting brackets included	617
AXIS M5525-E 50HZ	1	200		01145-001	01145-001	01145-001	Discreet PTZ with HDTV 1080p, 1920x1080, 10x optical zoom, automatic day/night and autofocus. Continues 360° pan. WDR- Forensic Capture, IP66, PoE and 24V . 30fps in H.264 and Motion JPEG, Zipstream, Scene profiles, two-way audio, 4 I/O. Surface mount or Axis PTZ standard mount. Midspan not included.	1,029
AXIS M5525-E 60HZ	1	150					Discreet PTZ with HDTV 1080p, 1920x1080, 10x optical zoom, automatic day/night and autofocus. Continues 360° pan. WDR- Forensic Capture, IP66, PoE and 24V . 30fps in H.264 and Motion JPEG, Zipstream, Scene profiles, two-way audio, 4 I/O. Surface mount or Axis PTZ standard mount. Midspan not included.	1,029
AXIS Q8665-LE 230V AC	1	1	Discontinued - contact Order dept for availability	0719-001	0719-001	0719-001	High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). External power supply with power input 230V AC and integrated light sensor for IR illuminator control included.	6,694
AXIS P5414-E 50HZ	1	15		0544-001	0544-001	0544-001	Intelligent Direct Drive PTZ camera with HDTV 720p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	1,647
AXIS P5414-E 60HZ	1	4					Intelligent Direct Drive PTZ camera with HDTV 720p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	1,647
AXIS P5415-E 50HZ	1	20		0546-001	0546-001	0546-001	Intelligent Direct Drive PTZ camera with HDTV 1080p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	2,059
AXIS P5415-E 60HZ	1	1				0589-001	Intelligent Direct Drive PTZ camera with HDTV 1080p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	2,059
AXIS Q8665-E 120V AC	1	1	Discontinued - contact Order dept for availability				High speed and precision PT-head design PTZ camera with integrated wiper. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 120V AC.	5,149
AXIS Q8665-E 230V AC	1	1	Discontinued - contact Order dept for availability	0716-001	0716-001	0716-001	High speed and precision PT-head design PTZ camera with integrated wiper. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 230V AC.	5,149

AXIS Q8665-LE 24V AC	1	1	Discontinued - contact Order dept for availability	0718-001	0718-001	0718-001	High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 24V AC.	5,355
AXIS Q8665-LE 120V AC	1	1	Discontinued - contact Order dept for availability				High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). External power supply with power input 120V AC and integrated light sensor for IR illuminator control included.	6,694
AXIS P5624-E MK II 50HZ	1	2		0931-001	0931-001	0931-001	PTZ camera with continues 360° pan for both indoor and outdoor with 23x optical zoom. HDTV 720p @ 25fps (1280x720) in H.264, Motion JPEG and Axis Zipstream and Focus Recall, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	1,647
AXIS P5624-E MK II 60HZ	1	30					PTZ camera with continues 360° pan for both indoor and outdoor with 23x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264, Motion JPEG and Axis Zipstream and Focus Recall, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	1,647
AXIS P5635-E MK II 50HZ	1	10	Discontinued - contact Order dept for availability	0930-001	0930-001	0930-001	PTZ camera with continues 360° pan for both indoor and outdoor with 30x optical zoom. Autofocus and Focus Recall. HDTV 1080p @ 25fps (1920x1080) in H.264, Motion JPEG and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	2,059
AXIS P5635-E MK II 60HZ	1	40	Discontinued - contact Order dept for availability				PTZ camera with continues 360° pan for both indoor and outdoor with 30x optical zoom. Autofocus and Focus Recall. HDTV 1080p @ 30fps (1920x1080) in H.264, Motion JPEG and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	2,059
AXIS P5655-E 50HZ	1	400		01681-001	01681-001	01681-001	PTZ camera with continues 360° pan for both indoor and outdoor with 32x optical zoom, Lightfinder 2, Autofocus and Focus Recall. HDTV 1080p @ 25/50fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	2,059
AXIS P5655-E 60HZ	1	150					PTZ camera with continues 360° pan for both indoor and outdoor with 32x optical zoom, Lightfinder 2, Autofocus and Focus Recall. HDTV 1080p @ 30/60fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	2,059
AXIS Q6000-E 50HZ MK II	1	1		01005-001	01005-001	01005-001	Outdoor-ready 360° situational awareness camera, comprising 4x2MP sensors @ 25fps in H.264 Zipstream and Motion JPEG. Tilttable sensors with exchangeable lenses. Designed to be integrated with any AXIS Q60-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	1,647

AXIS Q6000-E 60HZ MK II	1	4					Outdoor-ready 360° situational awareness camera, comprising 4x2MP sensors @ 30fps in H.264 Zipstream and Motion JPEG. Tilttable sensors with exchangeable lenses. Designed to be integrated with any AXIS Q60-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	1,647
AXIS Q6052 50HZ	1	1	Discontinued - contact Order dept for availability	0899-002	0899-006	0899-002	IP52, PTZ dome camera with 36x optical zoom. Lightfinder, Focus recall, Zipstream, WDR, EIS. Auto day/night functionality; min. illumination down to 0.15 lux in color and 0.008 in black/white. Continuous 360° rotation and 180° tilt with E-flip. Progressive scan, D1 resolution @ 50 fps in H.264 and Motion JPEG. Shock detection, autotracking, Active Gatekeeper, tour recording. Full size SD slot. Two way audio, four I/Os and external power with multi-connector cable (not included). Includes High PoE midspan with, smoked and clear dome covers, and mounting kits for hard and drop ceilings	2,162
AXIS Q6052 60HZ	1	1	Discontinued - contact Order dept for availability				IP52, PTZ dome camera with 36x optical zoom. Lightfinder, Focus recall, Zipstream, WDR, EIS. Auto day/night functionality; min. illumination down to 0.15 lux in color and 0.008 in black/white. Continuous 360° rotation and 180° tilt with E-flip. Progressive scan, D1 resolution @ 60 fps in H.264 and Motion JPEG. Shock detection, autotracking, Active Gatekeeper, tour recording. Full size SD slot. Two way audio, four I/Os and external power with multi-connector cable (not included). Includes High PoE midspan, smoked and clear dome covers, and mounting kits for hard and drop ceilings	2,162
AXIS Q6052-E 50HZ	1	1	Discontinued - contact Order dept for availability	0901-002	0901-006	0901-002	Outdoor-ready, IP66, 2599IK10 and NEMA 4X classification. PTZ dome camera with 36x optical zoom. Arctic Temperature Control enables operation and start up from -50 °C to +50 °C (-58 °F to 122 °F). Lightfinder, Focus recall, Zipstream, WDR, EIS. Auto day/night functionality; min. illumination down to 0.15 lux in color and 0.008 in black/white. Continuous 360° rotation and 220° tilt with E-flip. Progressive scan, D1 resolution @ 50 fps in H.264 and Motion JPEG. Shock detection, Autotracking, Active Gatekeeper, tour recording. Full size SD slot. Power through High PoE only. Includes clear transparent dome cover and High PoE midspan with fiber slot. No mounting bracket included (several different accessories available).	2,677
AXIS Q6052-E 60HZ	1	1	Discontinued - contact Order dept for availability				Outdoor-ready, IP66, IK10 and NEMA 4X classification. PTZ dome camera with 36x optical zoom. Arctic Temperature Control enables operation and start up from -50 °C to +50 °C (-58 °F to 122 °F). Lightfinder, Focus recall, Zipstream, WDR, EIS. Auto day/night functionality; min. illumination down to 0.15 lux in color and 0.008 in black/white. Continuous 360° rotation and 220° tilt with E-flip. Progressive scan, D1 resolution @ 60 fps in H.264 and Motion JPEG. Shock detection, Autotracking, Active Gatekeeper, tour recording. Full size SD slot. Power through High PoE only. Includes clear transparent dome cover and High PoE midspan with fiber slot. No mounting bracket included (several different accessories available).	2,677
AXIS Q6054 Mk III 50HZ	1	40	Discontinued - contact Order dept for availability	01481-002	01481-006	01481-002	HDTV 720p compliant, high-speed PTZ dome camera with 30x optical zoom for indoor use. HDTV 720p @ 25 fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP52. Continuous 360° rotation and 220° tilt with E-flip. Lightfinder, Focus recall, Zipstream, WDR, EIS, Automatic Defogging, shock detection. Full-size SD slot. Two-way audio, four I/Os and external power with multi-connector cable (not included). Includes High PoE midspan, smoked and clear dome covers, and mounting kits for hard and drop ceilings.	2,162

AXIS Q6054-E Mk III 50HZ	1	100	Discontinued - contact Order dept for availability	01483-002	01483-006	01483-002	HDTV 720p compliant, outdoor-ready, high-speed PTZ dome camera with 30x optical zoom. HDTV 720p @ 25fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66, IK10 and NEMA 4X classification. Continuous 360° rotation and 220° tilt with E-flip. Lightfinder, Focus recall, Zipstream, WDR, EIS, automatic defogging, shock detection, Arctic Temperature Control enables operation and start up from from -50 °C to +50 °C (-58 °F to 122 °F). Active Gatekeeper, tour recording and autotracking. Includes High PoE midspan with fiber slot and clear dome cover. Mounting brackets are not included (several different accessories available)	2,677
AXIS Q6055 50HZ	1	40	Discontinued - contact Order dept for availability	0907-002	0907-006	0907-002	HDTV 1080p compliant, high-speed PTZ dome camera with 32x optical zoom for indoor use. HDTV 1080p (1920x1080)@25 fps, 720P@50fps. Continuous 360° rotation and 220° tilt with E-flip. Day & Night, IP52, Zipstream, Shock detection, autotracking, tour recording and Active Gatekeeper. Two-way audio, I/O and external power with multi-connector cable (not included). Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection Includes High PoE midspan, smoked and clear dome covers, and mounting kits for hard and drop ceilings	2,625
AXIS Q6055 60HZ	1	20	Discontinued - contact Order dept for availability				HDTV 1080p compliant, high-speed PTZ dome camera with 32x optical zoom for indoor use. HDTV 1080p (1920x1080)@30 fps, 720P@60fps. Continuous 360° rotation and 220° tilt with E-flip. Day & Night, IP52, Zipstream, Shock detection, autotracking, tour recording and Active Gatekeeper. Two-way audio, I/O and external power with multi-connector cable (not included). Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection Includes High PoE midspan, smoked and clear dome covers, and mounting kits for hard and drop ceilings	2,625
AXIS Q6055-E 50HZ	1	1	Discontinued - contact Order dept for availability	0909-002	0909-006	0909-002	Top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 32x optical zoom and Zipstream. Arctic Temperature Control enables operation and start up from -50 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080)@25 fps, 720P@50fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Power through High PoE only. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	3,192
AXIS Q6055-E 60HZ	1	40	Discontinued - contact Order dept for availability				Top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 32x optical zoom and Zipstream. Arctic Temperature Control enables operation and start up from -50 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080)@30 fps, 720P@60fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Power through High PoE only. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	3,192

AXIS Q6055-C 50HZ	1	5		0942-001	0942-001	0942-001	Actively cooled, outdoor-ready high-speed PTZ dome camera with 32x optical zoom. IP66-, MIL-, IK10 and NEMA 4X-rated. Temperature range -20 °C to +75 °C. Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 25 fps. 720P@50 fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Including 5 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24 V in. Power supply and brackets are not included. (several different accessories available).	4,222
AXIS Q6055-C 60HZ	1	1					Actively cooled, outdoor-ready high-speed PTZ dome camera with 32x optical zoom. IP66-, MIL-, IK10 and NEMA 4X-rated. Temperature range -20 °C to +75 °C. Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 30 fps. 720P@60 fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Including 5 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24 V in. Power supply and brackets are not included. (several different accessories available).	4,222
AXIS Q6055-S 50HZ	1	8		0944-001	0944-001	0944-001	Stainless steel, (SS-316L) pressurized (5psi) Top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 32x optical zoom. Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 25 fps, 720@50 fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24V in. Brackets and power adapter are not included (several different accessories available).	4,634
AXIS Q6055-S 60HZ	1	1					Stainless steel, (SS-316L) pressurized (5psi) Top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 32x optical zoom. Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 30 fps, 720@60 fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24 V in. Brackets and power adapter are not included (several different accessories available).	4,634
AXIS Q6074 50HZ	1	20	New	01967-002	01967-006	01967-002	Top performance PTZ camera with HDTV 720p @50fps 30x optical zoom for indoor use. IP52 rated. Zpstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics: object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	2,162

AXIS Q6074 60HZ	1	7	New				Top performance PTZ camera with HDTV 720p @60fps 30x optical zoom for indoor use. IP52 rated. Ziptream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	2,162
AXIS Q6074-E 50HZ	1	100	New	01973-002	01973-006	01973-002	Top performance PTZ camera with HDTV 720p @60fps, 30x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Ziptream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	2,677
AXIS Q6074-E 60HZ	1	8	New				Top performance PTZ camera with HDTV 720p @60fps, 30x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Ziptream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	2,677
AXIS Q6075 50HZ	1	30	New		01749-006	01749-002	Top performance PTZ camera with HDTV 1080p @50fps 40x optical zoom for indoor use. IP52 rated. Ziptream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	2,625
AXIS Q6075 60HZ	1	50	New				Top performance PTZ camera with HDTV 1080p @50fps 40x optical zoom for indoor use. IP52 rated. Ziptream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	2,625

AXIS Q6075-E 50HZ	1	300	New		01751-006	01751-002	Top performance PTZ camera with HDTV 1080p @50fps, 40x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	3,192
AXIS Q6075-E 60HZ	1	20	New				Top performance PTZ camera with HDTV 1080p @60fps, 40x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	3,192
AXIS Q6124-E 50HZ	1	10	Discontinued - contact Order dept for availability	01069-003	01069-006	01069-002	Lightfinder HDTV PTZ for outdoor as well as indoor use. HDTV 720p resolution in 50fps with 30x zoom and top performance. Perfect image quality in all directions, without distortion. 130db WDR, EIS, automatic defog, Advanced gate keeper. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan with fiber slot included.	2,780
AXIS Q6124-E 60HZ	1	30	Discontinued - contact Order dept for availability				Lightfinder HDTV PTZ for outdoor as well as indoor use. HDTV 720p resolution in 60fps with 30x zoom and top performance. Perfect image quality in all directions, without distortion. 130db WDR, EIS, automatic defog, Advanced gate keeper. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan with fiber slot included.	2,780
AXIS Q6128-E 50HZ	1	30		0800-003	0800-006	0800-002	Compact, top performance 4K Comparable with SMPTE 2036 3840x2160 resolution in 25fps, (8MP). With 12x optical zoom for outdoor as well as indoor use. Day/night, Automatic defog, DNR 2D/3D and EIS. IP66, Active gatekeeper, tour recording and autotracking. Perfect image quality in all directions, without distortion, repaintable surface. Mounting brackets are not included (several different accessories available). Midspan with fiber slot included	3,295
AXIS Q6128-E 60HZ	1	2					Compact, top performance 4K Comparable with SMPTE 2036 3840x2160 resolution in 30fps, (8MP). With 12x optical zoom for outdoor as well as indoor use. Day/night, Automatic defog, DNR 2D/3D and EIS. IP66, Active gatekeeper, tour recording and autotracking. Perfect image quality in all directions, without distortion, repaintable surface. Mounting brackets are not included (several different accessories available). Midspan with fiber slot included.	3,295
AXIS Q6154-E 50HZ	1	20		01510-003	01510-006	01510-002	Compact top performance HDTV PTZ for outdoor and indoor use with unique Laser Focus giving perfect focus. HDTV 720p resolution in 50fps, perfect image quality in all directions without distortion due to Axis' Sharpdome technology with hard coating. Repaintable surface, will easily blend into the surroundings. 30x zoom 120dbWDR, EIS, automatic defog, Advanced gate keeper and Lightfinder. Midspan with fiber slot included	2,780

AXIS Q6154-E 60HZ	1	60					Compact top performance HDTV PTZ for outdoor and indoor use with unique Laser Focus giving perfect focus. HDTV 720p resolution in 60fps, perfect image quality in all directions without distortion due to Axis' Sharpdome technology with hard coating. Repaintable surface, will easily blend into the surroundings. 30x zoom 120dbWDR, EIS, automatic defog, Advanced gate keeper and Lightfinder. Midspan with fiber slot included	2,780	
AXIS Q6155-E 50HZ	1	10			0933-003	0933-006	0933-002	Compact top performance HDTV PTZ for outdoor and indoor use with unique Laser Focus giving perfect focus. HDTV 1080p resolution in 25fps, perfect image quality in all directions without distortion due to Axis' Sharpdome technology with hard coating. Repaintable surface, will easily blend into the surroundings. 30x zoom 120dbWDR, EIS, automatic defog, Advanced gate keeper and Lightfinder. Midspan with fiber slot included	3,089
AXIS Q6155-E 60HZ	1	30						Compact top performance HDTV PTZ for outdoor and indoor use with unique Laser Focus giving perfect focus. HDTV 1080p resolution in 30fps, perfect image quality in all directions without distortion due to Axis' Sharpdome technology with hard coating. Repaintable surface, will easily blend into the surroundings. 30x zoom 120dbWDR, EIS, automatic defog, Advanced gate keeper and Lightfinder. Midspan with fiber included	3,089
AXIS Q6215-LE 50HZ	1	30			01083-003	01083-006	01083-002	PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300n), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521. Camera part; 1/2" sensor with HDTV 1080p, 30x optical zoom, 50fps, H264 with Zipstream and Motion JPEG, WDR. Perfect image quality in all directions without distortion, window wiper. Advanced gate keeper analytics. 90W Midspan included. Color; Urban grey.	3,604
AXIS Q6215-LE 60HZ	1	8						PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300n), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521. Camera part; 1/2" sensor with HDTV 1080p, 30x optical zoom, 60fps, H264 with Zipstream and Motion JPEG, WDR. Perfect image quality in all directions without distortion, window wiper. Advanced gate keeper analytics. 90W Midspan included. Color; Urban grey.	3,604
AXIS V5914 60HZ	1	15						Generic PTZ camera with 30x zoom, autofocus and HDTV 720p resolution at 60fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, WDR, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. CD-audio quality in stereo. Compliance with SMPTE 296M Power supply and wall mount bracket are included.	2,059
AXIS V5915 50HZ	1	50			0633-003	0633-006	0633-002	Generic PTZ camera with 30x zoom, autofocus and HDTV 1080p resolution at 50fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, WDR, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. CD-audio quality in stereo. Compliance with SMPTE 274M Power supply and wall mount bracket are included.	2,677
AXIS V5914 50HZ	1	15			0631-003	0631-006	0631-002	Generic PTZ camera with 30x zoom, autofocus and HDTV 720p resolution at 50fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, WDR, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. CD-audio quality in stereo. Compliance with SMPTE 296M Power supply and wall mount bracket are included.	2,059
AXIS V5915 60HZ	1	20						Generic PTZ camera with 30x zoom, autofocus and HDTV 1080p resolution at 60fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, WDR, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. CD-audio quality in stereo. Compliance with SMPTE 274M Power supply and wall mount bracket are included.	2,677