



Bizgram Asia Pte Ltd

Retail Wholesale Factory Outlet Address :  
 #05-50 Sim Lim Square  
 1 Rochor Canal Road  
 Singapore 188504









Tel : +65-63346455 / 63341373  
 Fax : +65-63341615

SMS / Whatsapp : +65 - 8889 0955 / 8777 6955

Please send whatsapp to check stocks and timing, and any other details before visiting the store. As stocks situation might vary and price is for reference only and might change anytime due to any situation.

Solution		Quick Temporary Deployment System - Dom & Bullet Camera					
Recommended scene		Hospital, school, police station, government, enterprise zone, airport, railway station, bus station, metro station and other security check entrances for temporary control					
No	Picture	Basic model	General	Installation requirements	Recommended bracket accessories	Remark	Warranty
1		DS-2TD2636B-15/P	Thermal: 384 × 288; <b>Lens: 15mm</b> ; FOV: 24.2°×18.4°; Optical: 2688 × 1520; Lens: 6mm; Video mode: Bi-spectrum image fusion; Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C	Installation height: 1.7m~2.5m Face distance: 3~5m	Integrated wire hiding box: DS-1260ZJ: 302700239 Wall corner bracket: DS-1276ZJ-SUS: 302701678 Pole mounted: DS-2904ZJ : 302701930 Tripod: DS-2907ZJ: 302702952	1.Support AI human body detection, multiple targets detect body temperature at the same time 2. 160 series support audio alarm, built-in speaker, alarm voice rise when the body temperature is too high, 'body temperature abnormal, please recheck body temperature' 3. Various solutions are available: Accuracy of blackbody scheme is ± 0.3°C; Accuracy of non-blackbody scheme is ± 0.5°C, 4. Quick control, support tripod with easy installation	3 years
2		DS-2TD2636B-10/P	Thermal: 384 × 288; <b>Lens: 9.7mm</b> ; FOV: 37.5°×28.5°; Optical: 2688 × 1520; Lens: 4mm; Video mode: Bi-spectrum image fusion; Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C	Installation height: 1.7m~2.5m Face distance: 2~7m			3 years
3		DS-2TD2636B-13/P	Thermal: 384 × 288; <b>Lens: 13mm</b> ; FOV: 28.2°×21.3°; Optical: 2688 × 1520; Lens: 4mm; Video mode: Bi-spectrum image fusion; Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C	Installation height: 1.7m~2.5m Face distance: 2~7m			3 years
4		DS-2TD2617B-6/PA	Thermal: 160 × 120; <b>Lens: 6mm</b> ; FOV: 25°×18.7°; Optical: 2688 × 1520; Lens: 8mm; Video mode: Bi-spectrum image fusion; Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C	Installation height: 1.5m Face distance: 1.5m	Integrated wire hiding box: DS-1260ZJ: 302700239 Wall corner bracket: DS-1276ZJ-SUS: 302701678 Pole mounted: DS-2904ZJ : 302701930 Tripod: DS-2907ZJ: 302702952	3 years	
5		DS-2TD2617B-3/PA	Thermal: 160 × 120; <b>Lens: 3mm</b> ; FOV: 50°×37.2°; Optical: 2688 × 1520; Lens: 4mm; Video mode: Bi-spectrum image fusion; Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C	Installation height: 1.5m Face distance: 1.0m			3 years
6		DS-2TD1217B-6/PA	Thermal: 160 × 120; <b>Lens: 6mm</b> ; FOV: 25°×18.7°; Optical: 2688 × 1520; Lens: 8mm; Video mode: Bi-spectrum image fusion; Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C	Installation height: 1.5m Face distance: 3m	Wall mount bracket: DS-1273ZJ-140: 302700333 Wall corner bracket: DS-1276ZJ-SUS: 302701678 Junction box: DS-1280ZJ-DM21: 302700398 Tripod: DS-2907ZJ: 302702952 Wall mount with junction box : DS-1273ZJ-140B: 302700330	3 years	
7		DS-2TD1217B-3/PA	Thermal: 160 × 120; <b>Lens: 3mm</b> ; FOV: 50°×37.2°; Optical: 2688 × 1520; Lens: 4mm; Video mode: Bi-spectrum image fusion; Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C	Installation height: 1.5m Face distance: 1.0m			3 years
8		DS-2TE127-G4A	Temperature resolution: 0.1°C Accuracy: ±0.1°C Temperature stability: ±0.1°C/h Effective emissivity: 0.97±0.02 Operating temperature: 0~30°C	Installation height: 1.7m		The black body is matched with a tube machine / hemisphere trial, 1.2m away from the camera, and the elevation angle is 20°, to ensure that the black body appears in the upper left / upper right corner of the camera view. Make sure that it cannot be blocked by other targets during temperature measurement	2 years

Solution		Quick Temporary Deployment System - Handheld Camera					
Recommended scene		Highway exits, train cabin, airplane cabins etc. for flexible detection					
9		DS-2TP21B-6AVF/W	Thermal: 160 × 120, 6.2mm, 25° × 19° Visible: 2MP Bi-spectrum image fusion; WiFi, Audio alarm Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C IP54	Installation height: 1.5m Face distance: 1.0m			3 years
10		DS-2TP21B-6AVF (Without Wifi)	Thermal: 160 × 120, 6.2mm, 25° × 19° Visible: 2MP Bi-spectrum image fusion; Audio alarm Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C IP54				3 years
11		DS-2TP31B-3AUF	Thermal: 160 × 120 ; Accuracy: ±0.5°C Range: 30-45°C Working temperature: 10~35°C	Installation height: 1.5m Face distance: 1.0m			3 years
Accessories for all the Quick Temporary Deployment System							
12		DS-2907ZJ	UNC 1/4" -20 Tripod connection			As domestic suppliers have not fully restored production capacity recently, there are multiple suppliers, and there may be slight differences under the same model, which will not affect the use. If customers are concerned about this , we recommend that they purchase the products locally which meet the standards.	3 years
13		DS-2908ZJ	Turret-Tripod adapter	Tripod adapter, use it with a tripod.			3 years
14		DS-2909ZJ	Bullet-Tripod adapter	Tripod adapter, use it with a tripod.			3 years